

Technical Data Sheet

1. Product and Introduction

| | |
|---------------------|--|
| Product Name | L312T |
| Backing Material | Polyester Film |
| Bonding | Resin over Resin |
| Mineral Type | Premium Aluminum Oxide (heat treated, tough) |
| Coating State | Open coat + Top coat |
| Manufacturing Width | 1340mm |

2. Available Grit

| | | | | | | | | | | | | |
|------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|
| Grit | 16 | 24 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 |
| | | | | | | | | | | ● | ● | ● |
| | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 |
| | ● | △ | ● | △ | ● | △ | ● | ● | ● | ● | ● | ● |

◀ Rough(Grinding)

Finishing(Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit

3. Advantage

- ◆ Excellent cutting performance without clogging.
- ◆ Perfect sanding surface.
- ◆ Longer lasting with Durability.
- ◆ Especially, excellent for contour sanding without folding.

4. Operation / Application

- ◆ Discs, Long files..
- ◆ Automotive refinishing.
- ◆ White wood & Painted surface.

5. Work pieces

- ◆ Automobile.
- ◆ Wood (White & Painted).

6. Available Sander / Grinder

- ◆ Vibrator.
- ◆ Long file.
- ◆ Orbital sander.