DOORBELL 2GIG-DBELL1-345





The 2GIG Doorbell (2GIG-DBELL1-345) is a dual-purpose doorbell that can be installed with the dwelling's existing 24 V wiring or using the 345 MHz radio frequency:

When installed as a wired doorbell with the home's existing 24 AC wiring, the bell is fully water-resistant and the push button remains illuminated. When installed as a wireless doorbell, it features a fully water-resistant button. It communicates with the control panel using the 345 MHz frequency. The push button does not remain illuminated.

SPECIFICATIONS

Wireless Signal Range	350 ft (106.7 m) open air, with 2GIG Wireless Control Panel
Code Outputs	Alarm; Alarm Restore; Supervisory; Low Battery
Transmitter Frequency	345.000 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Supervisory Interval	70 minutes
External Input Sampling Current	20 uA
External Input	24V AC Standard Doorbell Circuit
Dimensions (L x W x H)	2.75 x 1.17 x 0.63 in. (6.99 x 2.97 x 1.60 cm)
Weight (including battery)	1.1 oz (31.2 g)
Housing Material	ABS Plastic
Color	White
Operating Temperature	14° to 104° F (-10° to 40° C)
Relative Humidity	5-95% Non-Condensing
Battery (included, not installed)	One (1) Panasonic CR 2032 3V or equivalent Lithium battery
Certification	Anatel, ETL, FCC, IC, IFETEL, and NOM

Nortek Security & Control | 1950 Camino Vida Roble Suite 150 | Carlsbad, CA 92008 | USA | 800.421.1587 | nortekcontrol.com | dealer.2gig.com

Copyright © 2015 Nortek Security & Control. All Rights Reserved. Linear and GolControl are registered trademarks of Linear LLC. All other products or name brands are either trademarks or registered trademarks of their respective holders. Specifications and product availability subject to change without notice. For more information, contact your local Nortek Security & Control or 2GIG dealer for pricing or visit nortekcontrol.com or dealer.2gig.com.

