

## 5816OD Wireless Outdoor Contact/Transmitter

### FAQs



<p>Since this is an outdoor product, what are the temperature and humidity ranges?</p>	<p>Temp -40° F to 150° F 100% RH (-40° C to 66° C) (UL rated at 85% RH)</p>
<p>What type of outdoor rating does the product have?</p>	<p>The weather-proof and water-resistant 5816OD has passed NEMA 4X water protection. NEMA 4X Rating: Intended for indoor or outdoor use primarily to provide a degree of protection against corrosion, windblown dust and rain, splashing water, hose directed water and to be undamaged by the formation of ice on the enclosure.</p>
<p>What is the wireless range of the product?</p>	<p>Range is dependent upon of the type of construction and number of walls that the signal must pass through. We anticipate over 200 foot range in a typical installation. If additional range is needed, a repeater (5800RP) can be added.</p>
<p>What is the gap of the product?</p>	<p>1.75" on wood, vinyl and non-metallic surfaces and 1.25" on steel.</p>
<p>What is the anticipated battery life?</p>	<p>Battery life is based upon the number of transmissions per day. On a typical installation we anticipate approximately five years with lithium batteries.</p>
<p>Is the battery replaceable?</p>	<p>Yes, the device will indicate when it has a low battery condition. Replace with two Energizer® E2 AA lithium batteries.</p>
<p>Do outside weather conditions affect range?</p>	<p>No.</p>
<p>Can the device be painted?</p>	<p>Yes, however we recommend using specific paint designed for plastic surfaces. Krylon® "Fusion for Plastic", Rust-Oleum® "Plastic" or Dupli-Color® "Vinyl and Fabric Coating".</p>
<p>Can the device be mounted on steel?</p>	<p>Yes. In the case of a metal shed, the device should be mounted on the outside of the shed to prevent loss of range.</p>