5897-35

WIRELESS DUAL TEC® MOTION SENSOR







Honeywell's 5897-35 Wireless Dual Tec® Motion Sensor provides reliable detection with improved false alarm immunity for tough commercial environments.

FEATURES

- Microwave/PIR Technology
- Automatic Walk Test

- Pet Alley and Barrier Lens Included
- Wireless Technology

SPECIFICATIONS

Detection Method

- Microwave 2.45 GHz
- Dual element passive infrared
- Coverage
 - 35' x 30' (11m x 9m)

Detection Zones

- 24 Zones (11 long range, 7 intermediate, 4 lower, 2 look-down)
- Optional Lenses (Included)
 - Barrier lenses 35' x 11' (11m x 3m)
 - Pet Alley 35' x 30' (11m x 9m)
- Sensitivity
 - 2-4 Steps


• Temperature compensation

- Temperature compensation adjusts for ambient temperature for improved performance
- Automatic Walk mode
 - Enabled simply by opening and closing the cover. After eight minutes, normal operation is resumed

- Microwave Range Adjustable
- Microwave Supervision
- Mounting Height
 - 7ft. 6 inches
- Power
 - Four 3V Batteries (included)
 - Replace only with: Honeywell/Ademco #466. Panasonic CR123A, Sanyo CR123A, Duracell DL123A or Varta CR123A (Lithium Manganese Dioxide)
- Case Tamper protection
- Operating Temperature
 - 32° to 140°F (0°C to +60°C)
- Operating Humidity
 - Up to 95% RH (max), non-condensing
- PIR White Light Immunity
 - ->4000 Lux
- RIF Immunity
- 30V/M, 10 MHz 1000 MHz

Dimensions

- 2 7/8" W x 5" H x 2 5/16" D (max protrusion) (7cm x13cm x 6cm)
- Compatibility
 - Compatible with all 5800 Series wireless devices
- Agency Listings
 - FCC, IC, Ctick, cULus



ORDERING

5897-35 Wireless DUAL TEC Motion Sensor

Honeywell Security & Custom Electronics

Honeywell International Inc. P.O. Box 9035 Syosset, NY 11791 www.honeywell.com

PI 06013 L/589735/D August 2006 ©2006 Honeywell International Inc.



35'