



Uplink 700FL Features:

Compact indoor design

802.11n wireless and 10/100 Base-T

Ethernet modes

True day vision, night vision

Built-in infrared (IR) LEDs for enhancing low light performance

Motion detection to trigger video recording

Specifications subject to change without notice.

Indoor Camera with Night Mode

SENSOR AND LENS	
Image Sensor	1/5" CMOS sensor
Minimum Illumination	
	0 Lux (with IR LED)
Lens	 Fixed-focal, aperture F2.0 Diagonal view angle: 61° (horizontal=50°, vertical=39°)
VIDEO	
Live view	QVGA (320x240) resolution, MJPEG compression, 3 frames per second
Recording	VGA (640x480) resolution, H.264 compression, 5 frames per second
Alarm & Event Mgmt.	Video motion detection
NETWORK	
Ethernet	10/100 Base-T, auto-MDIX
Protocols	IPv4, ICMP, DHCP, UDP, TCP/IP, DNS, NTP, FTP
Wireless	IEEE802.11b/g/n, WEP64/128 bit, WPA/WPA2 personal, WPS
HARDWARE	
Connectors	RJ-45 for Ethernet, DC power jack
Processors and Memory	 SoC: ARM9, 300M Hz RAM: 128 MB Flash: 16 MB
LED and Button	LED: Power, networkButton: WPS/reset
Night Vision	IR LED x 10 Light sensor x 1
Power Supply	100-240VAC, 50-60Hz (input), 12V, 1A (output)
Power Consumption	5.8W Max.
Compliance	CE, FCC, UL (power supply)
Dimensions (H x W x D)	4.9 x 3.1 x 2.6 in. (123 x 79 x 67 mm) – with stand
Weight	0.9 lb. (0.4 kg)
ENVIRONMENT	
Operation Temperature	32° - 104°F (0° - 40°C); humidity: 0% - 80% RH (non-cond.)
Storage Temperature	-4° - 158°F (-20° - 70°C); humidity: 0% - 90% RH (non-cond.)
VIDEO SERVICE	
Bronze	Live view
Silver	Live view + up to 500MB (typically 7 days) of storage
Gold	Live view + up to 2GB (typically 30 days) of storage
ORDERING INFORMATION	
Model Number	700FL
Package Contents	Camera, power supply, extension cord, lan cable, stand, hardware manual, Uplink video camera quick install guide

(888) 9-UPLINK | (888) 987-5465 | www.uplink.com | sales@uplink.com

