

uplink[®] CDMA50








CDMA ALARM COMMUNICATOR

FULL DATA/DIAL CAPTURE

The Uplink CDMA50 delivers full-event reporting and complete end-to-end signal verification for primary cellular communications or as a backup to land line connections. It uses the industry standard CDMA network, is compatible with virtually all security system panels and supports all common event reporting formats. Installation is remarkably easy, with no additional programming or central station equipment required. Instant onsite activation is available through the Uplink dealer website or live operator.

KEY FEATURES:

-  CDMA technology - not subject to 2G sunset.
-  Backup or primary cellular alarm/full event reporting
-  Contact ID, SIA, Modem IIe/IIIa/IIIa², or Pulse 4/2 (:10, :20, or :40 PPS) Formats
-  Installs in minutes with complete end-to-end signal verification
-  Instant activation by secure dealer website or live operator



SUPPORTS UPLINK REMOTE FOR INTERACTIVE CONTROL

UPLINK CDMA50 DEVICE FEATURES:

- ✓ U.S. and Canada coverage
- ✓ Telephone line monitoring for backup communications
- ✓ Programmable for primary communications
- ✓ Dial-capture, two inputs, three outputs and trouble reporting for universal compatibility
- ✓ Power from AC transformer. Supports backup battery
- ✓ Programmable monthly, weekly, or daily test options
- ✓ Works with any central station - no programmer required
- ✓ Expert support from a live technical specialist 8am-8pm Monday through Friday
- ✓ Flat-rate billing for improved dealer profitability

uplink[®] CDMA50

(888) 9-UPLINK | (888) 987-5465
www.uplink.com
sales@uplink.com



UPLINK CDMA50 ALARM COMMUNICATOR 16.5V 45VA Transformer Required

A TRUSTED PARTNER

The Uplink CDMA50 is a member of the Uplink family of wireless alarm communicators. Our products deliver the unique combination of reliable technology and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996. GSM or CDMA protocols, primary or back-up applications, summary or full data reporting, there is an Uplink wireless alarm communicator for virtually any security system on the market today. With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink delivers on its promise as the security dealer's trusted partner.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and a dealer web management tool.

For more information, visit the Uplink website and sign up to become an Uplink dealer at www.uplink.com.



INPUTS	
Alarm Dial Capture	Contact ID, SIA, Modem IIe/IIIa/IIIa ² , or Pulse 4/2 (:10, :20, or :40 PPS) formats
Two Inputs	3 configurable contact closures
OUTPUTS AND REPORTING	
Central Station	Contact ID, SIA, Modem IIe/IIIa/IIIa ² , or Pulse 4/2, Internet or Dial Up
Three Relay Outputs	3 Configurable Outputs
Other Reporting	<ul style="list-style-type: none"> • Low Battery • AC Loss • Panel (Not Default Settings) • Cable Supv. • Telco Loss • Watchdog
Automated Testing	Monthly, Weekly, or Daily
Status LEDs	<ul style="list-style-type: none"> • CDMA Network • Signal Strength • Power • Telco Line • Trouble • Heartbeat
POWER REQUIREMENTS	
AC Transformer	Use 16V AC 45VA Transformer - Not Included
Battery Backup	Use 12V DC, 1.4 AH. Battery Size: (max) L: 3.8, W: 1.7, H: 2.3 (PS1212 or equivalent)
Power Supply	Built-in, 12V DC Power Supply with battery backup & charging circuit
RADIO	
CDMA	U.S. and Canada
DIMENSIONS	
Height	10.5 x 5.4 x 2.5 inches
Antenna	3.75 inches
DEALER WEBSITE	
	Activate & Deactivate units Adjust settings and reporting Request status and signal strength View signal history Control inputs and outputs and notifications