

Panic Button technical specification.

Modified on: Thu, 27 Jul, 2017 at 10:12 PM

This page lists the technical specifications for Panic Button and form part of the larger **[Panic Button user guide.](https://aeotec.freshdesk.com/solution/articles/6000177086-panic-button-user-manual-)**
 [\(https://aeotec.freshdesk.com/solution/articles/6000177086-panic-button-user-manual-\)](https://aeotec.freshdesk.com/solution/articles/6000177086-panic-button-user-manual-)

Name: Panic Button

Model Number: DSA38

Dimensions: 2.2 x 1.2 x 0.5 inches

Weight: 0.8 oz

Repeater: No

Beaming: No

Number of Buttons: 1

Type of Control:

Direct Association (manual programming)

Scene Control (control gateway scenes)

Battery: lithium cell CR2450 3 volt battery

Operating temperature:

-10 C to 50 C.

14 F to 122 F.

Operating humidity: 8% to 80%

Operating distance:

Up to 300 feet outdoors.

Up to 100 metres outdoor.

Supported Commands.

- ☐ COMMAND_CLASS_ZWAVEPLUS_INFO
- ☐ COMMAND_CLASS_VERSION
- ☐ COMMAND_CLASS_MANUFACTURER_SPECIFIC
- ☐ COMMAND_CLASS_CONFIGURATION
- ☐ COMMAND_CLASS_BATTERY
- ☐ COMMAND_CLASS_ASSOCIATION
- ☐ COMMAND_CLASS_ASSOCIATION_GRP_INFO
- ☐ COMMAND_CLASS_POWERLEVEL
- ☐ COMMAND_CLASS_DEVICE_RESET_LOCALLY
- ☐ COMMAND_CLASS_WAKE_UP
- ☐ COMMAND_CLASS_MARK
- ☐ COMMAND_CLASS_SCENE_ACTIVATION
- ☐ COMMAND_CLASS_SWITCH_MULTILEVEL