



BAT LTE

Universal Internet & Cellular 4G LTE Alarm Communicator

SKU: IPD-BAT-LTE

With ipDatatel's industry unique Dual-Path alarm communicators, you can provide your customers with the best solutions while protecting your business against future cellular sunsets. Features the very latest in cellular technology, remote panel programming and universal panel support - including Honeywell, DSC and GE/Caddx/Concord 4 & Concord 4 Express. The BAT LTE's Dual Hi-Gain Antennas can increase cellular range by up to 50% compared to a single antenna.



DUAL PATH

Internet & Cellular alarm communications



UNIVERSAL PANEL COMPATIBILITY

Works with most alarm systems with Contact ID



SIMPLE INSTALLATION

Ethernet and pre-activated cellular



REMOTE PANEL PROGRAMMING

Saves time and virtually eliminates costly truck rolls



EVENT NOTIFICATIONS

Get alerts via text/push, email and digital voice call



CONTROL ON THE GO

Arm/disarm the system using a mobile device or PC















PANEL COMPATIBILITY

Works with most keyswitch connected panels using CID, including HAI OmniPro, Napco,

Honeywell

Honeywell Vista series panels are fully supported

Vista 20P/PS/PCN Vista 10P VISTA 10PSIA Vista 20PI Vista 128BP Vista 20PSIA Vista 128BPE/FB/FBPE Vista 21IP/IPSIA Vista 128FBP Vista 32FB Vista 128SIA First Alert FA130 Vista 15 First Alert FA148 Vista 15CN/P/PCN First Alert FA168 Vista 15PSIA Safewatch Pro 3000

DSC

Basic Signal only	Full Support
PC1555	PC1616
Alexor	PC1832
Impassa	PC1864
Neo	



Basic Signal only	Full Support*
Nx 4v1	Nx 4v2
Nx 6v1	Nx 6v2
Nx 8v1	Nx 8v2
Nx 8E	Concord 4
	Concord 4 Express

*Upload/Download not supported

TECHNICAL SPECIFICATIONS

RADIO:

Frequencies LTE 4G 700 MHz/1700MHz/1900MHz

POWER:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

ENVIRONMENTAL:

- Temperature Range
 30° to +70° C
 (- 22° to +158° F)
- Humidity0 to 95% non-condensing

PHYSICAL:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

