

Garage Door Controller technical specifications.

Modified on: Fri, 10 Mar, 2017 at 12:06 AM

This page lists the technical specifications for **Garage Door Controller** (<http://aeotec.com/z-wave-garage-door-controller>) and form part of the larger **Garage Door Controller user guide**. (<https://aeotec.freshdesk.com/solution/articles/6000053811-garage-door-controller-gen-5-user-guide->)

Name: Garage Door Controller

Model Number: ZW062

Repeater: Yes

Beaming: Yes

AES128 Security: Yes

Z-Wave Plus Certified: Yes

Power Supply:

Garage Door Controller

5V DC Adapter.

Tilt Sensor

CR2 Lithium battery 3V

800mA.

Max Alarm Power: 2W.

Standby Power: 0.7W

Operating humidity: 8% to 80%.

Operating temperature:

0°C to 40°C

32°F to 104°F.

Operating distance:

Up to 492 feet outdoors.

Up to 150 metres outdoors.

Supported Commands.

	Non-Secure	Secure
--	------------	--------

Node Info Frame	<p>COMMAND_CLASS_ZWAVEPLUS_INFO V2 COMMAND_CLASS_SWITCH_BINARY V1 COMMAND_CLASS_CONFIGURATION V1 COMMAND_CLASS_ASSOCIATION_GRP_INFO V1 COMMAND_CLASS_ASSOCIATION V2 COMMAND_CLASS_MANUFACTURER_SPECIFIC V2 COMMAND_CLASS_VERSION V2 COMMAND_CLASS_FIRMWARE_UPDATE_MD V2 COMMAND_CLASS_POWERLEVEL V1 COMMAND_CLASS_BARRIER_OPERATOR, COMMAND_CLASS_NOTIFICATION_V4, COMMAND_CLASS_SECURITY V1 COMMAND_CLASS_MARK V1 COMMAND_CLASS_APPLICATION_STATUS, COMMAND_CLASS_DEVICE_RESET_LOCALLY V1 COMMAND_CLASS_HAIL V1</p>	<p>COMMAND_CLASS_ZWAVEPLUS_INFO V2 COMMAND_CLASS_VERSION V2 COMMAND_CLASS_MANUFACTURER_SPECIFIC V2 COMMAND_CLASS_SECURITY V1 COMMAND_CLASS_MARK V1 COMMAND_CLASS_APPLICATION_STATUS, COMMAND_CLASS_DEVICE_RESET_LOCALLY V1 COMMAND_CLASS_HAIL V1</p>
Security Command Supported Report Frame		<p>COMMAND_CLASS_SWITCH_BINARY V1 COMMAND_CLASS_CONFIGURATION V1 COMMAND_CLASS_ASSOCIATION_GRP_INFO V1 COMMAND_CLASS_ASSOCIATION V2 COMMAND_CLASS_FIRMWARE_UPDATE_MD V2 COMMAND_CLASS_POWERLEVEL V1 COMMAND_CLASS_BARRIER_OPERATOR COMMAND_CLASS_NOTIFICATION_V4</p>