

Water Sensor 6 technical specification.

Modified on: Tue, 22 Aug, 2017 at 9:28 AM

This page lists the technical specifications for Water Sensor 6 and form part of the larger **[Water Sensor 6 user guide.](https://aeotec.freshdesk.com/solution/articles/6000171886-water-sensor-6-user-guide-)**
 [\(https://aeotec.freshdesk.com/solution/articles/6000171886-water-sensor-6-user-guide-\)](https://aeotec.freshdesk.com/solution/articles/6000171886-water-sensor-6-user-guide-)

Name: Water Sensor 6 / Water Sensor 6 Dock

Model number: ZW122

Z-Wave Plus Certified: Yes

Configuration Sheet: **[Download](https://aeotec.freshdesk.com/helpdesk/attachments/6051698050)** (<https://aeotec.freshdesk.com/helpdesk/attachments/6051698050>)

Buzzer Max Volume: 60dB from 2 meters

Sensors:

Air Temperature

Water Flow

Supported Notification Types:

Heat Alarm

Home Security

Water Alarm

Power supply:

CR123A lithium battery

3V / 1500mA

Repeater: No

Operating humidity: 8% to 80%.

Operating temperature:

0°C to 40°C

32°F to 104°F.

Storage Temperature: -20C to 60C

Water proofing: IP65 rating

Battery Life:

CR123A, 3V, 1500mAh.

2.3 years with default settings with estimated leakage events 5 times per month..

Operating distance:

Up to 492 feet outdoors.

Up to 150 metres outdoors.

Supported Command Classes.
Association Group Information
Association V2
Battery
Configuration
Device Reset Local
Firmware Update MD V2
Manufacturer Specific V2
Multi-Channel_V4
Multi-Channel-Association_V2

Notification V4
Powerlevel
Security
Sensor Multilevel V5
Version V2
Wake-Up V2
Z-Wave Plus Info V2