

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

1 Identification

- Product identifier

- **Trade name:** Vibra-TITE® Thread Sealant
- **Synonyms:** 486 Multi-Purpose Thread Sealant
- **Part number:** VT486
- **Application of the substance / the mixture**
Sealing
Sealant

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com
- **Information department:** Product safety department
- **Emergency telephone number:**
United States: 1-800-424-9300
International: +1-703-527-3887

* 2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02 GHS08

- Signal word

- **Signal word** Danger

- Hazard-determining components of labeling:

ethanol
titanium dioxide

- Hazard statements

H225 Highly flammable liquid and vapor.
H350 May cause cancer.

- Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 1)

P405
P501Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.**- Classification system:****- NFPA ratings (scale 0 - 4)****- HMIS-ratings (scale 0 - 4)****- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 64-17-5	ethanol	Flam. Liq. 2, H225; Carc. 1A, H350	20 – 29%
CAS: 63148-65-2	Binding agent	Skin Irrit. 2, H315; Combustible Dust	5 – 9%
CAS: 13463-67-7	titanium dioxide	Carc. 2, H351	1 – 4%
CAS: 9002-84-0	Polytetrafluoroethylene	Combustible Dust	1 – 4%

4 First-aid measures

- Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed** No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
CO₂, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents: Water with full jet**- Special hazards arising from the substance or mixture** No further relevant information available.**- Advice for firefighters****- Protective equipment:**

Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.**- Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

- Handling:

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

- **Breathing equipment:**

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Viscous

- **Color:**

Whitish

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 3)

- pH-value:	Not determined.
- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	≥ 78 °C (≥ 172.4 °F)
- Flash point:	13 °C (55.4 °F)
- Flammability (solid, gaseous):	Not applicable.
- Ignition temperature:	425 °C (797 °F)
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:	
- Lower:	3.5 Vol %
- Upper:	15 Vol %
- Vapor pressure at 20 °C (68 °F):	≤ 59 hPa (≤ 44.3 mm Hg)
- Density at 20 °C (68 °F):	~ 0.97475 g/cm ³ (~ 8.13429 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	20.0 %
- Water:	0.2 %
- VOC content:	20.00 %
	~ 195.0 g/l / ~ 1.63 lb/gal
- Solids content:	50.0 %
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	> 16,507 mg/kg (rat)
Inhalative	LC50/4 h	> 244 mg/l (rat)

CAS: 64-17-5 ethanol

Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 4)

CAS: 13463-67-7 titanium dioxide

Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

- Primary irritant effect:**- on the skin:** No irritant effect.**- on the eye:** No irritating effect.**- Sensitization:** No sensitizing effects known.**- Additional toxicological information:****- Carcinogenic categories****- IARC (International Agency for Research on Cancer)**

CAS: 14807-96-6	Soapstone	3
CAS: 64-17-5	ethanol	1
CAS: 13463-67-7	titanium dioxide	2B
CAS: 9002-84-0	Polytetrafluoroethylene	3

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information**- Toxicity****- Aquatic toxicity:** No further relevant information available.**- Persistence and degradability** No further relevant information available.**- Behavior in environmental systems:****- Bioaccumulative potential** No further relevant information available.**- Mobility in soil** No further relevant information available.**- Additional ecological information:****- General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment**- PBT:** Not applicable.**- vPvB:** Not applicable.**- Other adverse effects** No further relevant information available.**13 Disposal considerations****- Waste treatment methods****- Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**- Uncleaned packagings:****- Recommendation:** Disposal must be made according to official regulations.***14 Transport information****- UN-Number****- DOT**

UN1133

- IMDG, IATA

UN1170

- UN proper shipping name**- DOT**

Adhesives

- IMDG

ETHANOL (ETHYL ALCOHOL) mixture

- IATA

ETHANOL mixture

- Transport hazard class(es)**- DOT****- Class**

3 Flammable liquids

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 5)

- Label	3
- IMDG, IATA	
	
- Class	3 Flammable liquids
- Label	3
- Packing group	
- DOT, IMDG, IATA	II
- Environmental hazards:	
- Marine pollutant:	No
- Special precautions for user	Warning: Flammable liquids
- Danger code (Kemler):	33
- EMS Number:	F-E,S-D
- Stowage Category	A
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1170 ETHANOL (ETHYL ALCOHOL) MIXTURE, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

Soapstone

Castor oil

ethanol

Binding agent

titanium dioxide

Polytetrafluoroethylene

Alumina Trihydrate

Deionized water

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 6)

- Chemicals known to cause developmental toxicity:		
CAS: 64-17-5	ethanol	
- Carcinogenic categories		
- EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
- TLV (Threshold Limit Value established by ACGIH)		
CAS: 14807-96-6	Soapstone	A4
CAS: 64-17-5	ethanol	A3
CAS: 13463-67-7	titanium dioxide	A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 13463-67-7	titanium dioxide	
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs

- **Contact:** Safety, Health and Environmental Affairs

- **Date of preparation / last revision** 03/06/2019 / 19

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Carc. 1A: Carcinogenicity – Category 1A
 Carc. 2: Carcinogenicity – Category 2

- * **Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
 ®Vibra-TITE is a registered trademark of ND Industries, Inc.