



# SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## 1. Identification

### 1.1. Product identifier

Product Name 920FS WHITE

#### Other means of identification

Other information Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant  
Restrictions on use No information available

### 1.3. Details of the supplier of the safety data sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

### 1.4. Emergency telephone number

Emergency Telephone Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)  
**Rocky Mountain Poison Center:** 1-866-767-5089  
CHEMTREC (Chemical Transportation Emergency Center)

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 4

#### Hazards not otherwise classified (HNOC)

Not applicable

### 2.2. Label elements

#### EMERGENCY OVERVIEW

#### Danger

#### Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
Suspected of causing cancer

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

May cause damage to organs through prolonged or repeated exposure  
Combustible liquid



**Appearance** Paste

**Physical state** Liquid

**Odor** Solvent

## Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing must not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from flames and hot surfaces. - No smoking

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
IF ON SKIN: Wash with plenty of water and soap  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing  
If experiencing respiratory symptoms: Call a POISON CENTER or doctor  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

## Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep cool

## Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

43 % of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

Causes mild skin irritation.

## 3. Composition/information on ingredients

### 3.1. Substances

Not applicable.

### Mixture

Chemical name	CAS No	Weight-%
Polyvinyl chloride	9002-86-2	10 - 30
Limestone	1317-65-3	5 - <10
Titanium dioxide	13463-67-7	1 - <5
Propylene carbonate	108-32-7	1 - <5

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

Xylenes (o-, m-, p- isomers)	1330-20-7	1 - <5
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - <1
Ethylbenzene	100-41-4	0.1 - <1
Methylenediphenyl diisocyanate	26447-40-5	0.1 - <1
Quartz	14808-60-7	0.1 - <1

*\*The exact percentage (concentration) of composition has been withheld as a trade secret*

## 4. First-aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a physician. May cause allergic respiratory reaction. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. May produce an allergic reaction. Get immediate medical advice/attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required. See section 8 for more information. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.
-----------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization by inhalation and skin contact. May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

## 5. Fire-fighting measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b> Large Fire	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Hydrochloric Acid. Sulfur oxides.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

## 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment as required. See section 8 for more information. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Avoid breathing vapors or mists. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

**Other information** Refer to protective measures listed in Sections 7 and 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams. Stop leak if you can do it without risk. Do not touch or walk through spilled material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up** Use personal protective equipment as required. Take precautionary measures against static discharges. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **7. Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Handle in accordance with good industrial hygiene and

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

safety practice. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Do not breathe vapor or mist. Use with local exhaust ventilation. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

**Recommended storage temperature** Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

## 7.3 References to other sections

**Reference to other sections** Section 13: DISPOSAL CONSIDERATIONS  
Section 10: STABILITY AND REACTIVITY

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Polyvinyl chloride 9002-86-2	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	-	-
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Ethylbenzene 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**920FS WHITE**  
**Revision Number 3**

**Revision date 25-Aug-2022**  
**Supersedes Date: 22-Nov-2021**

Methylenediphenyl diisocyanate 26447-40-5	-	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m <sup>3</sup>	-
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

Chemical name	Argentina	Brazil	Chile	Colombia
Polyvinyl chloride 9002-86-2	-	TWA: 1 mg/m <sup>3</sup>	-	TWA: 1mg/m <sup>3</sup>
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	LPP: 7 mg/m <sup>3</sup> LPP: 5 mg/m <sup>3</sup>	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup>	-	TWA: 0.2mg/m <sup>3</sup> TWA: 2.5mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	LPP: 87 ppm LPP: 380 mg/m <sup>3</sup> LPT: 150 ppm LPT: 651 mg/m <sup>3</sup>	TWA: 20ppm
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	LPP: 87 ppm LPP: 380 mg/m <sup>3</sup> LPT: 125 ppm LPT: 543 mg/m <sup>3</sup>	TWA: 20ppm
Methylenediphenyl diisocyanate 26447-40-5	TWA: 0.005 ppm	-	LPP: 0.004 ppm LPP: 0.045 mg/m <sup>3</sup>	-
Quartz 14808-60-7	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	LPP: 0.08 mg/m <sup>3</sup>	TWA: 0.025mg/m <sup>3</sup>

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Polyvinyl chloride 9002-86-2	TWA: 1mg/m <sup>3</sup>	-	1 mg/m <sup>3</sup> TWA (respirable particulate matter)	-
Titanium dioxide 13463-67-7	TWA: 10mg/m <sup>3</sup>	TWA: 10mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup> TWA (nanoscale, respirable particulate matter); 2.5 mg/m <sup>3</sup> TWA (finescale, respirable particulate matter)	TWA: 10 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100ppm STEL: 150ppm	STEL: 150ppm STEL: 651mg/m <sup>3</sup> TWA: 100ppm TWA: 434mg/m <sup>3</sup>	20 ppm TWA	Skin STEL: 150 ppm TWA: 100 ppm
Ethylbenzene 100-41-4	TWA: 20ppm	STEL: 125ppm STEL: 543mg/m <sup>3</sup> TWA: 100ppm TWA: 434mg/m <sup>3</sup>	20 ppm TWA	Skin STEL: 125 ppm TWA: 100 ppm
Quartz 14808-60-7	TWA: 0.025mg/m <sup>3</sup>	TWA: 0.05mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup> TWA (respirable particulate matter)	TWA: 0.025 mg/m <sup>3</sup>

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## 8.2. Exposure controls

### OTHER INFORMATION

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

Chemical name	Argentina	Brazil	Chile	Colombia
Methyl alcohol 67-56-1	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 156 ppm TWA: 200 mg/m <sup>3</sup> STEL: 250 ppm Skin	LPP: 175 ppm LPP: 229 mg/m <sup>3</sup> S* LPT: 250 ppm LPT: 328 mg/m <sup>3</sup>	STEL: 250ppm TWA: 200ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl alcohol 67-56-1	TWA: 200ppm STEL: 250ppm	STEL: 250ppm STEL: 328mg/m <sup>3</sup> TWA: 200ppm TWA: 262mg/m <sup>3</sup>	250 ppm STEL 200 ppm TWA	Skin STEL: 250 ppm TWA: 200 ppm

### Appropriate engineering controls

#### Engineering controls

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand protection

Impervious gloves.

#### Skin and body protection

Wear suitable protective clothing.

#### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General hygiene considerations

Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Do not breathe vapor or mist. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

recommended.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Color	White
Odor	Solvent
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	71 °C / 159.8 °F	
Evaporation rate	No data available	None known
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

### 9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	96	
Softening Point	No information available	
Molecular weight	No information available	
VOC content	2.7 %	No information available
Liquid Density	1.21 g/cm <sup>3</sup>	
Bulk density	No information available	

## 10. Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Chemical stability Stable under normal conditions.

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

**Hazardous polymerization** Hazardous polymerization may occur.

## 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks. Extremes of temperature and direct sunlight. Keep from any possible contact with water. Storage near to reactive materials.

## 10.5. Incompatible materials

**Incompatible materials** Water. Alcohols. Strong acids. Strong bases. Strong oxidizing agents. Finely powdered metals.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** Carbon monoxide Carbon dioxide (CO<sub>2</sub>) Nitrogen oxides (NO<sub>x</sub>) Hydrogen cyanide Thermal decomposition can lead to release of irritating and toxic gases and vapors Carbon oxides

## **11. Toxicological information**

### 11.1. Information on toxicological effects

#### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components).
<b>Eye contact</b>	Based on available data, the classification criteria are not met.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation".

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.

### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (dermal)</b>	24,400.60 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	132.40 mg/l
<b>ATEmix (inhalation-vapor)</b>	293.00 mg/l

#### Component Information

# SAFETY DATA SHEET

**920FS WHITE**  
**Revision Number 3**

**Revision date 25-Aug-2022**  
**Supersedes Date: 22-Nov-2021**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Propylene carbonate 108-32-7	LD50 > 5000 mg/kg (Rattus) OECD 401	> 3000 mg/kg (Oryctolagus cuniculus)	-
Xylenes (o-, m-, p- isomers) 1330-20-7	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h
Ethylbenzene 100-41-4	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.6 mg/L (Rattus) 4 h
Methylenediphenyl diisocyanate 26447-40-5	>10000 mg/kg (Rattus)	> 10000 mg/kg (Oryctolagus cuniculus)	=490 mg/m <sup>3</sup> (Rattus) 4 h
Quartz 14808-60-7	>20000 mg/kg	-	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

**Respiratory or skin sensitization** May cause sensitization by inhalation. May cause sensitization by skin contact.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	Not a skin sensitizer
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitizer

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	No sensitization responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for

# SAFETY DATA SHEET

**920FS WHITE**  
**Revision Number 3**

**Revision date 25-Aug-2022**  
**Supersedes Date: 22-Nov-2021**

ingredients. May cause cancer. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Polyvinyl chloride 9002-86-2	-	Group 3	-	-
Titanium dioxide 13463-67-7	A3	Group 2B	-	X
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X
Methylenediphenyl diisocyanate 26447-40-5	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

Methylenediphenyl diisocyanate (26447-40-5)

Method	Species	Results
	in vivo	Limited evidence of a carcinogenic effect

Quartz (14808-60-7)

Method	Species	Results
IARC (International Agency for Research on Cancer)	Human evidence	Carcinogenic

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT - single exposure**

Based on available data, the classification criteria are not met.

**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Target organ effects**

Blood, Central nervous system, Eyes, Gastrointestinal tract (GI), Kidney, Liver, Lungs, Respiratory system, Skin.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other adverse effects**

No information available.

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

Interactive effects No information available.

## 12. Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae ( <i>Desmodesmus subspicatus</i> )	CL50 (96h)>10000mg/L ( <i>Oncorhynchus mykiss</i> )	-	CE50 (48h) >1000 mg/L Daphnia Magna
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l ( <i>Cyprinodon variegatus</i> ) OECD 203	-	-	-
Propylene carbonate 108-32-7	ErC50 (72h): > 900mg/L ( <i>Desmodesmus subspicatus</i> , OECD-201)	LC50 (96) h > 1000 mg/L ( <i>Cyprinus carpio</i> , 67/548/EWG, Annex V, C.1.)	EC50 > 10000 mg/L 17 h	EC50 (48h): > 1000mg/L ( <i>Daphnia magna</i> , OECD 202)
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L ( <i>Oncorhynchus mykiss</i> ) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L ( <i>Daphnia magna</i> )
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L ( <i>Pseudokirchneriella</i> <i>subcapitata</i> )	LC50 96 h = 4.2 mg/L ( <i>Oncorhynchus mykiss</i> semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, <i>Daphnia magna</i> )
Methylenediphenyl diisocyanate 26447-40-5	EC50: =3230mg/L (96h, <i>Skeletonema costatum</i> )	-	-	EC50: >1000mg/L (24h, <i>Daphnia magna</i> )

### 12.2. Persistence and degradability

Persistence and degradability No information available.

### 12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

#### Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Propylene carbonate 108-32-7	-0.41
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6
Ethylbenzene 100-41-4	3.6
Methylenediphenyl diisocyanate 26447-40-5	4.5

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## 12.4. Mobility in soil

Mobility No information available.

## Other adverse effects

Other adverse effects No information available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

## 14. Transport information

**Note:** 49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant."

### DOT

UN number or ID number	NA1993
Proper Shipping Name	Combustible liquid, n.o.s.
Transport hazard class(es)	Combustible liquid
Packing Group	III
Reportable quantity - lbs	Chlorobenzene: RQ (lb)= 1, Xylenes (o-, m-, p- isomers): RQ (lb)= 100.00
Reportable Quantity (RQ)	(Chlorobenzene: RQ (kg)= 0.454, Xylenes (o-, m-, p- isomers): RQ (kg)= 45.40)
Special Provisions	IB3, T1, TP1, 148
Marine Pollutant	Np
Description	NA1993, Combustible liquid, n.o.s.(Xylenes (o-, m-, p- isomers), Ethylbenzene), III
Emergency Response Guide Number	128

**IATA** Not regulated

**IMDG** Not regulated

## 15. Regulatory information

### International Inventories

TSCA	Listed
DSL	Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### US Federal Regulations

US - EN

# SAFETY DATA SHEET

920FS WHITE  
Revision Number 3

Revision date 25-Aug-2022  
Supersedes Date: 22-Nov-2021

## SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers)	1330-20-7	1.0
Ethylbenzene	100-41-4	0.1
Methylenediphenyl diisocyanate	26447-40-5	1.0

## SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

## Europe

### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

## SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## 16. Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 25-Aug-2022

Revision Note SDS sections updated. 3. 4. 6. 7. 8. 10. 11. 12. 14.

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet