



# Safety Data Sheet

**SUPERTAK 807120 GP AEROSOL**  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product Name** SUPERTAK 807120 GP AEROSOL

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesives.  
**Uses advised against** No information available

### 1.3. Details of the supplier of the safety data sheet

#### **Responsible Party**

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

E-mail msds@bostik-us.com

### 1.4. Emergency telephone number

Telephone: 1-800-227-0332  
(Outside U.S.) 1-703-527-3887

## Section 2: HAZARD IDENTIFICATION

### 2.1. Classification of the substance or mixture

Serious Eye Damage/Eye Irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

### 2.2. Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

#### **Hazard statements**

Causes serious eye irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Extremely flammable aerosol

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017



Appearance Aerosol

Physical State Gas

Odor Solvent

## Precautionary Statements - Prevention

Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
Wear protective gloves/protective clothing/eye protection/face protection

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

## Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards Not Otherwise Classified (HNOC)

Not applicable

## Unknown acute toxicity

48% of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

No information available.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Methyl acetate	79-20-9	20 - 40
Propane	74-98-6	10 - 20
Acetone	67-64-1	10 - 20
n-Heptane	142-82-5	2.5 - 10

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

Dimethyl ether	115-10-6	2.5 - 10
1,1-Difluoroethane	75-37-6	2.5 - 10
Methylcyclohexane	108-87-2	0.1 - 1

*The exact percentage (concentration) of composition has been withheld as a trade secret.*

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If medical advice is needed, have product container or label at hand.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
<b>Ingestion</b>	If swallowed, call a poison control center or physician immediately. Rinse mouth. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
<b>Self-Protection of the First Aider</b>	Use personal protective equipment as required. Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Drowsiness. Dizziness. Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Irritating to eyes.
-----------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically. Keep victim under observation. Symptoms may be delayed.
---------------------------	--

### 4.4. Reference to Other Sections

<b>Reference to other sections</b>	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION Section 11: TOXICOLOGY INFORMATION
------------------------------------	--

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>).

#### **Unsuitable Extinguishing Media**

Strong water jet. Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

#### **Specific Hazards Arising from the Chemical**

In the event of fire and/or explosion do not breathe fumes. This product may retain a static electrical charge, which could produce a

# Safety Data Sheet

**SUPERTAK 807120 GP AEROSOL**  
**Revision Number 2**

**Revision Date 02-Jan-2018**  
**Supersedes Date: 03-Feb-2017**

spark. May be ignited by heat, sparks or flames. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition. Extremely flammable.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Formaldehyde.

**Explosion Data**  
**Sensitivity to Mechanical Impact** None.  
**Sensitivity to Static Discharge** May be ignited by friction, heat, sparks or flames.

### 5.3. Advice for firefighters

#### **Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do it without risk. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Contents under pressure. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Stop leak if you can do it without risk. Avoid breathing vapors or mists. Ensure adequate ventilation, especially in confined areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Other Information** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc) away from spilled material.

**For emergency responders** Use personal protective equipment as required. Remove all sources of ignition. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### 6.2. Environmental precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading.

**Methods for cleaning up** Use personal protective equipment as required. Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Following product recovery, flush area with water.

### 6.4. Reference to other sections

**Reference to other sections** Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
Section 13: DISPOSAL CONSIDERATIONS

## **Section 7: HANDLING AND STORAGE**

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

## 7.1. Precautions for safe handling

### Advice on safe handling

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. This material can accumulate static charge by flow or agitation and can be ignited by static discharge. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation and in closed systems. Pressurized container: Do not pierce or burn, even after use. Never pierce, drill, grind, cut, saw or weld any empty container. Do not reuse container. Avoid contact with skin, eyes or clothing. After contact with skin, wash immediately with plenty of water and soap.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage Conditions

Keep locked up and out of reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Recommended storage temperature. 10 - 35 °C. Observe local regulations / instructions for storage of pressurized containers. Use spark-proof tools and explosion-proof equipment. Do not reuse container. Store away from incompatible materials. See section 10 for more information.

### Incompatible Materials

Strong oxidizing agents. Strong acids. Chlorinated compounds. Acid anhydrides. Halogens.

## 7.3. Specific end use(s)

### Other Information

No information available.

## 7.4. References to Other Sections

### Reference to other sections

Section 13: DISPOSAL CONSIDERATIONS  
Section 10: STABILITY AND REACTIVITY

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	-
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> STEL: 1260 ppm STEL: 3000 mg/m <sup>3</sup>
n-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 1600 mg/m <sup>3</sup> STEL: 500 ppm STEL: 2000 mg/m <sup>3</sup>
Methylcyclohexane 108-87-2	TWA: 400 ppm	IDLH: 1200 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 1600 mg/m <sup>3</sup>

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

		TWA: 1600 mg/m <sup>3</sup>		STEL: 500 ppm STEL: 2000 mg/m <sup>3</sup>
--	--	-----------------------------	--	---

Chemical Name	Argentina	Brazil	Chile	Venezuela
Methyl acetate 79-20-9	TWA: 200 ppm STEL: 250 ppm	-	TWA: 175 ppm TWA: 530 mg/m <sup>3</sup>	STEL: 250 ppm TWA: 200 ppm
Propane 74-98-6	TWA: 2500 ppm	-	-	TWA: 1000 mg/m <sup>3</sup> TWA: 1000 ppm
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 780 ppm TWA: 1870 mg/m <sup>3</sup>	TWA: 438 ppm TWA: 1040 mg/m <sup>3</sup>	STEL: 750 ppm TWA: 500 ppm
n-Heptane 142-82-5	TWA: 400 ppm STEL: 500 ppm	-	-	STEL: 500 ppm TWA: 400 ppm
Dimethyl ether 115-10-6	-	-	-	TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup>
Methylcyclohexane 108-87-2	TWA: 400 ppm	-	-	TWA: 400 ppm

## 8.2. Exposure controls

### Engineering Controls

Showers  
Eyewash stations  
Ventilation systems. Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment [PPE]

#### Eye/Face Protection

Wear safety glasses with side shields (or goggles).

#### Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

#### Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General Hygiene Considerations

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Keep away from food, drink and animal feeding stuffs. Avoid contact with eyes, skin and clothing. Wash hands thoroughly after handling. Take off all contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Gas
Appearance	Aerosol
Color	White
Odor	Solvent
Odor Threshold	No information available

#### Property

#### Values

#### Remarks • Method

pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	50.44 °C / 122.78 °F	
Flash Point	-104.4 °C / -155.9 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	10.7	
Lower flammability limit:	2.1	

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

<b>Vapor Pressure</b>	No information available	<b>Water Solubility</b>	No information available
<b>Vapor Density</b>	No information available	<b>Solubility in Other Solvents</b>	No information available
<b>Relative Density</b>	No information available	<b>Partition Coefficient</b>	No information available
		<b>Autoignition Temperature</b>	No information available
		<b>Decomposition Temperature</b>	No information available
<b>Kinematic Viscosity</b>	No information available		
<b>Dynamic Viscosity</b>	No information available		
<b>Explosive Properties</b>	No information available		
<b>Oxidizing Properties</b>	No information available		
<b>9.2. Other information</b>			
<b>Softening Point</b>	No information available		
<b>Molecular Weight</b>	No information available		
<b>Solvent content (%)</b>	No information available		
<b>Solid content (%)</b>	No information available		
<b>Density</b>			
<b>VOC</b>	27.7 %		

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None under normal use conditions.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

### 10.4. Conditions to avoid

Heating causes rise in pressure with risk of bursting. Keep away from heat, sparks and flames. Incompatible Materials.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Chlorinated compounds. Acid anhydrides. Halogens.

### 10.6. Hazardous decomposition products

Carbon oxides. Formaldehyde. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## Section 11: TOXICOLOGY INFORMATION

### 11.1. Information on toxicological effects

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

<b>Product Information</b>	Harmful by inhalation
<b>Inhalation</b>	May cause drowsiness or dizziness. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin Contact</b>	No known effect based on information supplied.
<b>Ingestion</b>	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

## Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl acetate 79-20-9	> 5 g/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 ppm ( Rat ) 4 h
Propane 74-98-6	-	-	= 658 mg/L ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	>15800 mg/Kg (rat)	= 79 mg/l( Rat ) 4 h
n-Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h
Dimethyl ether 115-10-6	-	-	= 164000 ppm ( Rat ) 4 h
Methylcyclohexane 108-87-2	> 3200 mg/kg ( Rat )	>2920 mg/Kg bw (rat) 24 hour	>23 mg/l (vapour) (Rat- OECD 403)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Symptoms</b>	No information available.
<b>Skin Corrosion/Irritation</b>	Substance may cause slight skin irritation.
<b>Serious Eye Damage/Eye Irritation</b>	Severe eye irritation.
<b>Irritation</b>	No information available.
<b>Corrosivity</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>Reproductive Toxicity</b>	No information available.
<b>Developmental Toxicity</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - Single Exposure</b>	May cause drowsiness or dizziness.
<b>STOT - Repeated Exposure</b>	No information available.
<b>Chronic Toxicity</b>	Avoid repeated exposure. Prolonged exposure may cause chronic effects.
<b>Target Organ Effects</b>	Heart, Central nervous system, Eyes, Respiratory system, Skin.
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration). May be fatal if swallowed and enters airways.
<b>Carcinogenicity</b>	This product does not contain any carcinogens or potential carcinogens as listed by ACGIH, OSHA, IARC or NTP at or above 0.1 wt%.

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Methyl acetate 79-20-9	EC50 72 h > 120 mg/L (Desmodesmus subspicatus)	LC50 96 h 250 - 350 mg/L (Brachydanio rerio static) LC50 96 h 295 - 348 mg/L (Pimephales promelas)	EC50 = 6000 mg/L 16 h EC50 = 6100 mg/L 30 min	EC50 48 h = 1026.7 mg/L (Daphnia magna )



# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

		flow-through)		
Acetone 67-64-1		LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
n-Heptane 142-82-5		LC50 96 h = 375.0 mg/L (Cichlid fish )		EC50 24 h > 10 mg/L (Daphnia magna )
Methylcyclohexane 108-87-2	10 mg/l (Pseudokirchneriella subcapitata - OECD 201)	2.07 mg/l (Oryzias latipes )		3 mg/l (Daphnia magna - OECD 202)

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

## 12.4. Mobility in soil

No information available.

## Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### **Disposal of Wastes**

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

#### **Contaminated Packaging**

Dispose of in accordance with federal, state and local regulations

## Section 14: TRANSPORTATION INFORMATION

### **Note:**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition) The information shown here, may not always agree with the bill of lading shipping description for the material

### DOT

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Reportable Quantity (RQ)	(Acetone: RQ (kg)= 2270.00)
Special Provisions	N82
Description	UN1950, Aerosols, 2.1
Emergency Response Guide Number	126

### IATA

UN/ID No	UN1950
Proper Shipping Name	Aerosols, flammable
Transport hazard class(es)	2.1
ERG Code	10L
Special Provisions	A145, A167, A802
Description	UN1950, Aerosols, flammable, 2.1

### IMDG

# Safety Data Sheet

SUPERTAK 807120 GP AEROSOL  
Revision Number 2

Revision Date 02-Jan-2018  
Supersedes Date: 03-Feb-2017

UN Number	UN1950
Proper Shipping Name	Aerosols (n-Heptane), Marine Pollutant
Transport hazard class(es)	2.1
EmS-No	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959
Description	UN1950, Aerosols (n-Heptane), 2.1, Marine Pollutant

## Section 15: REGULATORY INFORMATION

### Global Inventories

TSCA	Listed
DSL	Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### WHMIS Hazard Class

A - Compressed gases  
B5 - Flammable aerosol  
D2B - Toxic materials



### United States of America

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

### Europe

#### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

#### EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No.

# Safety Data Sheet

**SUPERTAK 807120 GP AEROSOL**  
**Revision Number 2**

**Revision Date** 02-Jan-2018  
**Supersedes Date:** 03-Feb-2017

1907/2006 (REACH), Article 59)

## Section 16: OTHER INFORMATION

### Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

### Key Literature References and Sources for Data

No information available

<b>Prepared By</b>	Product Safety & Regulatory Affairs
<b>Revision Date</b>	02-Jan-2018
<b>Revision Note</b>	SDS sections updated, 1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15, 16.
<b>Training Advice</b>	No information available
<b>Further information</b>	No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**