



Clear Penetrating Grease



FEATURES

- High tack
- Quick penetrating action
- Resists water washout
- Protects against corrosion
- Metal detectable plastic components
- Clear lubricating gel

APPLICATIONS

- Bottling Equipment
- Bushings
- Cables
- Chains
- Door Hinges
- Food Machinery
- Fork Lifts
- Pistons
- Rails
- Rings
- Seals
- Slides
- Valves
- Wire Rope

SPECIFICATIONS AND APPROVALS

- NSF International, H1

PROPERTIES

Appearance/physical state	Gas/Aerosol
Odor	Acetone
Melting point/freezing point	Not available
Boiling point/range	132.8 °F (56 °C)
Vapor pressure	Not available
Partition coefficient	Not available
Percent volatile	41.50%
Flammability limit	Not available
Propellant	Petroleum Gases, Liquefied, Sweetened
VOC Content	24.5 % per U.S. State and Federal Consumer Product Regulations
Color	Beige
Flash point	132.8 °F (56.0 °C) Tag Closed Cup
Relative density	Not available
Evaporation rate	Not available
Vapor density	2 (air = 1)
Auto-ignition temperature	Not available
Viscosity	260 cP @ 75°F (concentrate)
Specific Gravity (water=1)	0.82
Temperature Range °F(°C)	0°F (-18°C) to 400°F (204°C)
4-Ball Weld Load	126 kg

DIRECTIONS

Shake well before using to insure proper mixing. Apply liberally. A thickened grease will form within seconds after application.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. (See Section 7 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. (See Section 13 of the SDS)

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
06716	C06716	11 wt oz	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved