

#743 SchaefferSeal™

Extreme Duty Tire Sealant



1. **SchaefferSeal™ coats the entire inner liner, wheel and bead area of the tire. It is a self-healing liquid inner tube that can easily be installed through the valve stem of any air filled tire**
2. Works in all air-filled tires.
3. Prevents flat tires with a permanent seal. Seals ¼" diameter punctures in tread area, much larger punctures up to ¾" in heavy ply tires.
4. Reduces fuel costs by maintaining recommended tire pressures.
5. Reduces premature tread wear caused by under inflation by as much as 52%.
6. Prevents porosity leaks, Rim and Bead leaks.
7. Reduces internal dry rot and deterioration by keeping tire casing moist and pliable.
8. Protects against rust and corrosion with anti-corrosion agents. These agents prevent corrosion of rims and steel tire belts. The sealant formulation itself also protects against rust, corrosion and pitting on the rim.
9. Maximizes and extends tire life by maintaining proper air pressures in tires. Properly inflated tires permit the correct amount of tread area to be in contact with the surface which reduces excessive tire flexing that can lead to tire failure.
10. Works as a thermal conductor, transferring heat away from areas of higher temperatures (the tread area), to areas of lower temperature (the sidewalls).
11. Effective in very cold temperatures down to -40°F and will not freeze until -70°F.
12. Does not affect tire balance in heavy duty tires when installed properly and spreads evenly over the inside of the tire which aids tire balance and provides a smooth, constantly protected ride.
13. Seals rim weld imperfections.
14. Reduces the risk of tire blowouts. Most tire blowouts are caused by tires being extremely underinflated. When the tire becomes underinflated the sidewall cannot withstand the flexing and overheating and blows out.
15. Effective for the life of the tire.
16. Stays pH neutral for the life of the tire.
17. Ready to use, no mixing, stirring, shaking or other special preparation needed.
18. The thixotropic advantage. SchaefferSeal™ will thin down when a tire is in motion, but rapidly thickens when the motion ceases, thereby maintaining an even layer of SchaefferSeal™ on the tire inner liner. SchaefferSeal™ will not separate, freeze or ball up. Its adhesion properties provide continuous coating action.





19. Chemically inert. Can be used with nitrogen filled tires. Will not react with the rubber in the tire or a metal wheel.
20. Fibers used to make the permanent plug: cotton, rayon, nylon, and ground pieces of polyethylene. These particulates are not water soluble, therefore they will not dissolve when the tire is driven in rain or snow; the plug is permanent.
21. SchaefferSeal™ based on "Standard Methods for the Examination of Water and Wastewater" American Public Health Association, 1992; California Title 22 Code, Section #66261.24(a) (6)' Static Acute Bioassay Procedures For Hazardous Waste Samples" (Polisini and Miller, 1988), California Department of Toxic Control (**CA, EPA**). SchaefferSeal™ was tested and found to be not environmentally hazardous.
22. Environmental Attorney John R. Spenser, (formerly REGION X Director of the United States Environmental Protection Agency Under two Presidents), concluded that SchaefferSeal™:
 - a. Is non-corrosive.
 - b. Is safe for disposal in landfill under the "most Strict" Washington State regulations.
 - c. Has passed the significant Washington State Bio-Assay Test.
23. SchaefferSeal™ meets or exceeds all criteria for being environmentally safe. The tests conducted on SchaefferSeal™ using the criteria specified by the United States Postal Service concluded that SchaefferSeal™ does not contain, asbestos, in any form, encapsulated or not, or any other substance which the Occupational Safety and Health Administration (**OSHA**) or the Environmental Protection Agency (**EPA**) might find harmful to Postal Service employees or the environment. SchaefferSeal™ does not contain hexavalent chromium, methyl, ethyl or isopropyl alcohol, or any material considered as hazardous by the EPA and does not present a waste disposal problem.
24. SchaefferSeal™ according to Smithers Scientific Services, reduced inner liner temperatures suggesting that the sealant acts as a heat sink, pulling heat out of the tread area.
25. 100% water soluble for easy clean out of a tire for recapping, boot or section patching if needed.
26. Indefinite shelf life, contents never separate out. SchaefferSeal™ is a homogenous mixture with the ingredients bonded together in such a manner that it is impossible for the ingredients to settle to the bottom.



Good people. Great products.

102 Barton Street
St. Louis, MO 63104
(800-325-9962)

www.schaefferoil.com



14 in. Rims			14.5 in. Rims			15 in. Rims			16 in. Rims			16.5 in. Rims			17 in. Rims			18 in. Rims			19 in. Rims			20 in. Rims		
225 / 50 - 14	22 oz.		MH 7.00 - 14.5	19 oz.		7.50 - 15	25 oz.		10.00 - 15	34 oz.		10.00 - 15	43 oz.		195 / 50 - 14	30 oz.		7.00 - 17	30 oz.		7.00 - 18	30 oz.		9.00 - 20	38 oz.	
245 / 50 - 14	24		MH 8.00 - 14.5	22		8.25 - 15	30		195 / 60 - 14	19		205 / 60 - 14	19		245 / 50 - 14	24		7.00 - 17	30 oz.		8.25 - 18	40 oz.		10.00 - 20	44 oz.	
265 / 50 - 14	27		MH 9.00 - 14.5	26		9.00 - 15	32		205 / 60 - 14	19		215 / 60 - 14	22		265 / 50 - 14	27		285 / 35 - 17	30		10.00 - 18	40		11.00 - 20	48 oz.	
255 / 55 - 14	27					10.00 - 15	34		215 / 60 - 14	22		225 / 60 - 14	24		295 / 50 - 16	30		315 / 35 - 17	32		12.00 - 18	40		11.50 - 20	49 oz.	
175 / 60 - 14	16					11.00 - 15	43		225 / 60 - 14	22		235 / 55 - 16	24		295 / 50 - 16	30		335 / 30 - 18	35		12.00 - 20	54		12.00 - 20	54 oz.	
185 / 60 - 14	16					195 / 50 - 15	30		235 / 60 - 14	24		245 / 50 - 16	26		295 / 50 - 16	30		245 / 35 - 18	34		13.00 - 20	60		13.00 - 20	60 oz.	
195 / 60 - 14	19					205 / 50 - 15	32		245 / 60 - 14	24		255 / 50 - 16	28		295 / 50 - 16	30		285 / 35 - 18	30		14.00 - 20	70		14.00 - 20	70 oz.	
205 / 60 - 14	19					265 / 50 - 15	32		255 / 60 - 14	27		265 / 50 - 16	30		295 / 50 - 16	30		225 / 40 - 17	30		16.00 - 20	85		16.00 - 20	85 oz.	
215 / 60 - 14	22					275 / 50 - 15	30		265 / 60 - 14	27		275 / 50 - 16	32		295 / 50 - 16	30		225 / 45 - 17	22		275 / 35 - 20	30		275 / 35 - 20	30 oz.	
225 / 60 - 14	22					295 / 50 - 15	32		275 / 60 - 14	27		285 / 55 - 16	24		295 / 50 - 16	30		235 / 45 - 17	24		255 / 40 - 20	27		255 / 40 - 20	27 oz.	
235 / 60 - 14	24					305 / 50 - 15	32		285 / 60 - 14	27		295 / 50 - 16	30		295 / 50 - 16	30		245 / 40 - 18	24		295 / 40 - 20	35		295 / 40 - 20	35 oz.	
245 / 60 - 14	24					305 / 50 - 15	32		295 / 60 - 14	27		305 / 55 - 16	26		295 / 50 - 16	30		255 / 45 - 17	27		335 / 80 - 22.5	44		335 / 80 - 22.5	44 oz.	
255 / 60 - 14	27					325 / 50 - 15	35		305 / 60 - 14	27		315 / 55 - 16	28		295 / 50 - 16	30		305 / 45 - 17	35		335 / 80 - 22.5	49		335 / 80 - 22.5	49 oz.	
265 / 60 - 14	27					325 / 50 - 15	35		315 / 60 - 14	27		325 / 55 - 16	30		295 / 50 - 16	30		305 / 45 - 17	35		365 / 80 - 22.5	54		365 / 80 - 22.5	54 oz.	
275 / 60 - 14	30					325 / 50 - 15	35		325 / 60 - 14	27		335 / 55 - 16	32		295 / 50 - 16	30		315 / 45 - 17	35		365 / 80 - 20					

OVER THE ROAD TIRES - CONTINUED

Small Trailers and Campers

8in. Rims		10 in. Rims		23.5x8.50-12	20	7.35-14	15	15in. Rims		8.25-15	20	7.00-16	20	9.50-16.5	25
4.8-8	10 oz.	6.50-10	16 oz.	13in. Rims		7.75-14	15	G78-15	26 oz.	8.55-15	20	7.50-16	20	10.00-16.5	30
5.70-8	10	7.00-10	16	6.00-13	15 oz.	7.90-14	16	H78-15	28	8.85-15	20	8.00-16	20	12.00-16.5	35
166x6.50-8	11	7.50-10	16	6.50-13	15	8.25-14	20	L78-15	29	9.00-15	20	8.25-16	25	17.5 in. Rims	
185x8.50-8	16	20.5x8.00-10	16	7.00-13	15	8.55-14	20	6.70-15	23	10.00-15	20	9.00-16	25	7.00-17.5	30 oz.
185x9.50-8	18	20.5x10-10	15	14 in. Rims		11-14	20	6.85-15	20	11.00-15	20	10.00-16	25	8.00-17.5	30
9in. Rims		12 in. Rims		E78-14	23 oz.	14.5 in. Rims		7.00-15	20	12.00-15	20	11.00-16	25	10.00-17.5	35
6.90-9	14 oz.	4.80-12	10 oz.	G78-14	22	7.00-14.5	20 oz.	7.10-15	20	16in. Rims		16.5 in. Rims			
		5.30-12	12	6.45-14	15	8.00-14.5	20	7.35-15	20	6.00-16	20 oz.	8.00-16.5	25 oz.		
		6.90-12	15	7.00-14	18	9.00-14.5	20	7.50-15	20	6.50-16	20	8.75-16.5	25		
								7.75-15	20						

Motorcycle / Dirt Bike Tires

4in. Rims		12 in Rims		180/80-14	18	100/80-16	9	5.10-17	12	160/60-17	16	100/80-18	10	3.60-19	9
3.00-4	4 oz.	2.50-12	4 oz.	15 in Rims		100/90-16	9	5.30-17	14	160/70-17	17	100/90-18	10	70/100-19	7
8in. Rims		3.00-12	5	2.50-15	5 oz.	110/70-16	10	5.60-17	15	170/60-17	17	100/100-18	10	90/90-19	9
3.00-8	4 oz.	25x8.00-12	20	5.10-15	12	110/90-16	11	70/100-17	6	180/55-17	18	110/80-18	11	90/100-19	9
3.5-8	4	60/100-12	4	120/70-15	10	120/80-16	11	80/60-17	7	190/50-17	19	110/90-18	11	100/90-19	10
4.00-8	6	80/100-12	6	130/90-15	13	120/90-16	12	100/80-17	9	200/50-17	20	110/100-18	12	110/80-19	11
10in. Rims		100/90-12	8	140/80-15	13	130/60-16	12	100/90-17	10	18 in. Rims		120/70-18	12	110/90-19	12
2.5-10	4 oz.	110/100-12	9	140/90-15	14	130/70-16	12	100/100-17	10	2.50-18	6 oz.	120/80-18	12	110/100-19	12
2.75-10	4	120/80-12	9	150/80-15	15	130/90-16	13	110/70-17	10	2.75-18	6	120/90-18	13	120/70-19	12
3.00-10	4	120/90-12	10	150/90-15	15	140/70-16	13	110/80-17	11	3.00-18	7	130/70-18	13	120/90-19	13
3.5-10	6	130/70-12	10	160/80-15	16	140/90-16	15	110/100-17	11	3.25-18	8	130/80-18	14	20 in. Rims	
4.00-10	7	13 in Rims		170/60-15	16	150/80-16	15	120/60-17	11	3.50-18	8	130/90-18	14	90/100-20	10 oz.
6.70-10	8	110/90-13	9 oz.	170/70-15	17	160/80-16	17	120/65-17	11	4.00-18	10	140/70-18	14	21 in. Rims	
19x6.00-10	11	150/70-13	13	170/80-15	18	170/70-16	17	120/70-17	11	4.10-18	10	140/80-18	15	2.75-21	7 oz.
19x7.00-10	13	14 in. Rims		180/70-15	18	180/60-16	18	120/80-17	12	4.25-18	11	150/60-18	15	3.00-21	8
24x11.00-10	26	2.25-14	4 oz.	16 in Rims		180/70-16	19	120/90-17	12	4.35-18	11	150/70-18	16	3.25-21	9
70/100-10	4	2.50-14	4	2.50-16	5 oz.	200/60-16	20	130/70-17	13	4.50-18	11	160/60-18	16	70/100-21	7
80/90-10	5	3.00-14	5	2.75-16	6	17 in. Rims		130/80-17	13	4.60-18	12	19 in. Rims		80/80-21	8
90/90-10	6	3.60-14	7	3.00-16	6	2.25-17	5 oz.	130/90-17	14	5.10-18	13	2.50-19	6 oz.	80/100-21	9
110/90-10	8	4.10-14	8	3.25-16	7	2.50-17	5	140/70-17	14	5.30-18	14	2.75-19	6	90/80-21	10
120/90-10	9	60/100-14	5	3.50-16	8	2.75-17	6	140/80-17	15	5.60-18	15	3.00-19	7	90/90-21	10
130/90-10	10	90/100-14	8	5.00-16	12	3.00-17	7	150/60-17	15	60/100-18	8	3.25-19	8	90/100-21	10
		120/80-14	10	90/90-16	8	3.50-17	8	150/70-17	15	90/90-18	9	3.50-19	8	23 in. Rims	
		160/60-14	14	90/100-16	8	4.60-17	11	150/80-17	16	90/100-18	9		8	3.00-23	8 oz.

Light Duty Tires (Autos, Light Trucks and Sport U.V.s)

This sealant should only be used as a temporary emergency fix for Light Duty High Speed Tires.

Vibration may occur at speeds over 40 mph. This water soluble sealant may be easily cleaned out, and the tire can still be plugged or patched.

15 Inch Rims or Smaller - 16 ounces

Larger than 15 Inch Rims - 24 ounces

ATV TIRES - Over 40 MPH

Formula for tire sizes not found in this section: **Over 40 Miles per Hour** - Tire Height x Full Tire Width ÷ (divided by) 10 = Ounces per tire

Under 40 Miles per Hour - Tire Height x Full Tire Width ÷ (divided by) 5 = Ounces per tire.

6 in. Rims		20x9.00-8	18	20x12.00-9	24	20x10.00-10	20	23x11.00-10	25	23x9.00-11	21	25x8.00-12	20	28x12.00-12	34
145/70-6	8 oz.	20x10.00-8	20	21x7.00-9	15	20x11.00-10	22	24x8.00-10	19	23.5x8.00-11	19	25x9.50-12	24	205/80-12	21
7 in. Rims		20x11.00-8	22	21x8.00-9	17	20x12.00-10	24	24x10.50-10	25	24x8.00-11	19	25x10.00-12	25	270/60-12	27
16x8.00-7	13 oz.	20x12.00-8	24	21x12.50-9	27	21x7.00-10	15	24x11.00-10	27	24x9.00-11	22	25x11.00-12	28	15.5 in. Rims	
18x7.00-7	13	21x9.00-8	19	22x8.00-9	18	21x8.00-10	17	24x11.50-10	28	24x9.50-11	22	25x12.50-12	31	27x9.00-15.5	25 oz.
8 in. Rims		21x10.00-8	21	22x10.00-9	22	21x9.00-10	19	24x12.00-10	29	24x10.00-11	24	26x9.00-12	23	(LSW 238-394)	
16x6.00-8	10 oz.	21x11.00-8	23	22x11.00-9	24	21x10.00-10	21	25x9.50-10	24	25x8.00-11	20	26x10.00-12	26	27x10.00-15.5	27
18x9.00-8	16	21x12.00-8	25	22x12.00-9	27	21x11.00-10	23	25x10.00-10	25	25x9.50-11	24	26x10.50-12	27	(LSW 255-394)	
18x9.50-8	17	21x12.50-8	27	22x12.50-9	28	21x12.50-10	27	25x11.00-10	28	25x10.00-11	25	26x12.00-12	31		
18x10.00-8	18	22x10.00-8	22	24x11.00-9	27	22x7.00-10	16	25x12.00-10	30	25x12.50-11	32	27x8.00-12	22		
18x10.50-8	19	22x11.00-8	24	25x12.00-9	30	22x8.00-10	18	25x12.50-10	31	26x12.00-11	29	27x9.00-12	24		
18x11.00-8	20	22x12.00-8	27	25x12.50-9	31	22x10.00-10	22	25x13.50-10	34	12 in. Rims		27x10.00-12	27		
18x11.50-8	20	22x12.50-8	28	25x13.00-9	33	22x11.00-10	24	26x12.00-10	31	23x8.00-12	18 oz.	27x11.00-12	30		
18x19.50-8	35	22.5x10.00-8	23	25x13.50-9	34	22x12.00-10	27	27x12.00-10	32	23x10.00-12	23	27x12.00-12	32		
19x7.00-8	13	9 in. Rims		10 in. Rims		22x12.50-10	28	11 in. Rims		24x8.00-12	19	28x8.00-12	22		
19x8.00-8	15	18x10.50-9	19 oz.	18x11.00-10	20 oz.	23x7.00-10	16	22x7.00-11	15 oz.	24x9.00-12	22	28x9.00-12	25		
19x9.50-8	18	20x10.00-9	20	20x6.00-10	12	23x8.00-10	19	22x10.00-11	22	24x11.00-12	26	28x10.00-12	28		
20x7.00-8	14	20x11.00-9	22	20x7.00-10	14	23x10.00-10	23	23x8.00-11	19	24x11.50-12	28	28x11.00-12	31		



Good people. Great products.



For questions or comments:

1.800.325.9962

Schaeffer Manufacturing Company

102 Barton Street, St. Louis, MO

63104

www.schaefferoil.com

OFF ROAD TIRES

Formula for tire sizes not found in this section...Tire Height x Full Tire Width ÷ (divided by) 5 = Ounces per tire

4 in. Rims		21 x 8.00 - 9	34	27 x 10.00 - 12	54	7.00 - 16	48	20 in. Rims		18.40 - 24	220	875 / 65 - 29	522	39 in. Rims		33.50 - 39	750 oz.
2.50 - 4	6 oz.	21 x 9.00 - 9	38	145 / 80 - 12	25	7.20 - 16	50	7.00 - 20	74 oz.	19.40 - 24	228	30 in. Rims		3.00 - 30	30 oz.	37.50 - 39	780
2.80 - 4	8	22 x 7.00 - 9	31	155 / 80 - 12	27	7.50 - 16	56	7.50 - 20	76	19.50L - 24	230	4.00 - 30	30 oz.	38.00 - 39	785	40 / 65 - 39	728
4.10 - 4	8	22 x 10.00 - 9	44	14 in. Rims		8.00 - 16	60	8.00 - 20	78	21.00L - 24	260	6.00 - 30	60	40 / 65 - 39	728	40.50 / 75 - 39	808
9 x 3.50 - 4	8	22 x 11.00 - 9	48	4.00 - 14	25 oz.	8.25 - 16	62	8.25 - 20	80	48 x 20.00 - 24	192	7.20 - 30	100	43.50 - 39	880	45 / 65 - 39	878
11 x 4.00 - 4	9	22 x 12.00 - 9	53	6.00 - 14	36	8.30 - 16	64	9.00 - 20	88	320 / 75 - 24	111	9.50 - 30	186	41.25 / 70 - 39	800	42 in. Rims	
5 in. Rims		24 x 13.00 - 9	62	7.00 - 14	40	9.00 - 16	70	9.50 - 20	90	420 / 70 - 24	160	11.00 - 30	224	43.50 - 39	880	45 / 65 - 39	878
3.40 - 5	8 oz.	25 x 11.00 - 9	55	7.50 - 14	45	9.50 - 16	74	10.00 - 20	92	540 / 65 - 24	225	24.5 in Rims		18.00 - 30	240	9.50 - 42	170 oz.
4.10 - 5	12	25 x 12.00 - 9	60	8.00 - 14	48	10.00 - 16	78	10.30 - 20	94	12.00 - 24.5	140	12.00 - 24.5	140	21.00 - 30	270	12.40 - 42	174
4.10 / 3.50 - 5	10	25 x 13.00 - 9	65	8.50 - 14	50	11.00 - 16	90	10.50 - 20	98	13.50 - 24.5	144	13.50 - 24.5	144	23.10 - 30	346	18.90 - 42	300
10 x 4.50 - 5	9	10 in Rims		9.00 - 14	55	11L - 16	90	11.00 - 20	100	7.5 - 25	90 oz.	14.00 - 25	156	67 x 34.00 - 30	456	18.40 - 42	310
10.5 x 5.00 - 5	11	3.00 - 10	16 oz.	9.50 - 14	60	11.20 - 16	90	11.20 - 20	100	90 oz.	130 oz.	15.00 - 25	165	380 / 85 - 30	170	20.80 - 42	330
11 x 3.50 - 5	8	3.50 - 10	18	9.5L - 14	64	11.50 - 16	96	11.20 - 20	100	11.00 - 25	130	16.00 - 25	170	420 / 90 - 30	202	480 / 80 - 42	277
11 x 4.00 - 5	9	4.50 - 10	20	11.00 - 14	65	12.40 - 16	98	11.50 - 20	102	12.00 - 25	138	17.50 - 25	215	480 / 70 - 30	218	520 / 85 - 42	322
11 x 4.50 - 5	10	6.50 - 10	35	11L - 14	74	12.50 - 16	98	12.50 - 20	106	13.00 - 25	146	18.00 - 25	215	540 / 65 - 30	251	580 / 70 - 42	346
11 x 5.00 - 5	13	7.00 - 10	35	13.00 - 14	80	12.5L - 16	98	13.00 - 20	128	14.00 - 25	156	20.00 - 25	220	620 / 70 - 42	381	650 / 65 - 42	394
11 x 6.00 - 5	15	7.50 - 10	38	23 x 8.50 - 14	39	13.60 - 16	102	14.00 - 20	146	14.00 - 25	165	22.65 - 25	236	8.30 - 32	98 oz.	710 / 70 - 42	464
11 x 7.00 - 5	17	9.00 - 10	44	25 x 8.50 - 14	43	33 x 9.50 - 16	63	16.00 - 20	160	15.00 - 25	170	23.00 - 25	240	9.50 - 32	104	900 / 50 - 42	562
11 x 7.50 - 5	17	15L - 10	60	70 - 14	36	215 / 85 - 16	53	18.00 - 20	170	16.00 - 25	186	23.50 - 25	240	10.00 - 32	148	43 in. Rims	
13 x 5.00 - 5	13	18 x 9.50 - 10	34	78 - 14	36	225 / 75 - 16	53	24.00 - 20	210	17.50 - 25	215	23.50 - 25	240	24.50 - 32	360	24.00 - 43	500 oz.
6 in. Rims		18 x 9.80 - 10	35	15 in. Rims		235 / 85 - 16	56	38 x 14.00 - 20	106	18.00 - 25	186	24.00 - 25	240	30.50 - 32	480	45 in. Rims	
4.00 - 6	12 oz.	18 x 10.00 - 10	36	4.00 - 15	26 oz.	245 / 75 - 16	60	38 x 18.00 - 20	137	20.00 - 25	220	24.00 - 25	240	30.50 - 32	480	45 / 65 - 45	932 oz.
4.10 - 6	12	18 x 10.50 - 10	38	5.00 - 15	30	255 / 85 - 16	68	41 x 14.00 - 20	115	21.00 - 25	220	24.00 - 25	240	33.50 - 32	520	65 / 45 - 45	1346
4.10 / 3.50 - 6	12	18 x 11.00 - 10	40	5.50 - 15	32	265 / 75 - 16	68	42 x 14.00 - 20	120	22.00 - 25	226	24.00 - 25	240	35.50 - 32	602	46 in. Rims	
5.30 - 6	20	20 x 7.50 - 10	30	6.00 - 15	36	13.50 - 16.1	128 oz.	44 x 18.00 - 20	158	22.65 - 25	236	24.00 - 25	240	36.50 - 32	620	13.60 - 46	210 oz.
6.90 / 6.00 - 6	25	20 x 8.00 - 10	32	6.40 - 15	40	14L - 16.1	130	44 x 41.00 - 20	360	23.00 - 25	240	23.50 - 25	240	37.50 - 32	640	14.90 - 46	236
8.00 - 6	22	20 x 10.00 - 10	40	6.70 - 15	42	14.5 / 75 - 16.1	110	47 x 25.00 - 20	235	23.50 - 25	240	23.50 - 25	240	38.00 / 95 - 46	177	18.40 - 46	312
12 x 6.00 - 6	14	20 x 11.00 - 10	44	7.00L - 15	52	16.5L - 16.1	160	48 x 25.00 - 20	240	23.50 - 25	240	23.50 - 25	240	38.00 / 90 - 46	223	230 / 95 - 46	117
12 x 8.00 - 6	19	20 x 12.00 - 10	48	7.5L - 15	54	18.4 - 16.1	186	48 x 26.50 - 20	254	24.00 - 25	240	23.50 - 25	240	38.00 / 90 - 46	223	340 / 85 - 46	188
12 x 11.00 - 6	26	20 x 14.00 - 10	56	7.60 - 15	54	19L - 16.1	186	48 x 31.00 - 20	298	25 / 55 - 25	263	24.00 - 25	240	420 / 80 - 46	245	480 / 80 - 46	295
13 x 5.00 - 6	13	20.50 - 10	39	8.15 - 15	59	21.5L - 16.1	220	50 x 20.00 - 20	200	25 / 65 - 25	288	24.00 - 25	240	520 / 85 - 46	338	47 in. Rims	
13 x 6.00 - 6	16	20.5 x 7.00 - 10	29	8.25 - 15	63	35 x 19.00 - 16.1	133	21 in. Rims		26.50 - 25	288	24.00 - 25	240	620 / 70 - 46	400	13.60 - 46	210 oz.
13 x 6.50 - 6	17	20.5 x 8.00 - 10	33	8.5 / 90 - 15	62	38 x 20.00 - 16.1	152	27.25 - 21	319 oz.	26.50 - 25	288	24.00 - 25	240	340 / 85 - 46	188	14.90 - 46	236
14 x 4.50 - 6	13	21 x 7.00 - 10	29	9.00 - 15	66	42 x 16.53 - 16.1	139	22 in. Rims		27.50 - 25	300	24.00 - 25	240	380 / 65 - 32	471	380 / 90 - 46	223
14 x 6.00 - 6	17	21 x 8.00 - 10	34	9.5L - 15	66	45 x 18.42 - 16.1	166	7.50 - 22	70 oz.	28.00 - 25	300	24.00 - 25	240	420 / 80 - 46	245	480 / 80 - 46	295
14 x 8.00 - 6	22	22 x 8.00 - 10	35	9.5L - 15	66	45 x 21.5L - 16.1	194	8.50 - 22	80	28.00 - 25	300	24.00 - 25	240	520 / 85 - 46	338	520 / 85 - 46	338
15 x 6.00 - 6	18	22 x 9.00 - 10	40	9.70 - 15	68	16.5 in. Rims		10.00 - 22	100	28.00 - 25	300	24.00 - 25	240	620 / 70 - 46	400	48 in. Rims	
16.00 x 4.50 - 6	14	22 x 10.00 - 10	44	10.00 - 15	76	10 - 16.5	78 oz.	10.00 - 22.5	76 oz.	28.00 - 25	300	24.00 - 25	240	33 in. Rims		18.00 - 33	294 oz.
145 / 70 - 6	16	22 x 11.00 - 10	48	11.00 - 15	78	12 - 16.5	86	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	21.00 - 33	370	49 in. Rims	
7 in. Rims		23 x 7.00 - 10	32	11L - 15	78	30.5 x 12.50 - 16.5	76	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	27.00 - 33	460	24.00 - 49	580
4.50 - 7	16 oz.	23 x 8.00 - 10	37	12.2L - 15	80	31 x 11.50 - 16.5	71	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	30.00 - 33	490	27.00 - 49	612
4.80 - 7	16	23 x 9.00 - 10	41	12.5L - 15	80	33 x 12.50 - 16.5	83	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	33.50 - 33	604	50 in. Rims	
8 in. Rims		23 x 10.00 - 10	46	13.50 - 15	90	33 x 14.50 - 16.5	96	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	35 / 65 - 33	550	230 / 95 - 48	120 oz.
ALL GOLF CARS	20 oz.	24 x 11.00 - 10	53	14.50L - 15	100	35 x 14.50 - 16.5	101	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	37.50 - 33	728	49 in. Rims	
4.00 - 8	16	25 x 8.00 - 10	40	18.25 - 15	120	36.5 x 12.50 - 16.5	91	10.00 - 22.5	76	28.00 - 25	300	24.00 - 25	240	11.20 - 34	150 oz.	18.00 - 49	360 oz.
4.30 - 8	17	25 x 11.00 - 10	55	25 x 7.50 - 15	38	16.7 in. Rims		15.00 - 22.5	106	28.00 - 25	300	24.00 - 25	240	12.40 - 34	170	21.00 - 49	440
4.80 - 8	18	25 x 12.00 - 10	60	25 x 9.00 - 15	45	7.00 - 17	42 oz.	15.00 - 22.5	106	28.00 - 25	300	24.00 - 25	240	14.90 - 34	196	24.00 - 49	580
5.00 - 8	21	27 x 9.00 - 10	49	25 x 10.50 - 15	53	7.50 - 17	46	15.00 - 22.5	106	28.00 - 25	300	24.00 - 25	240	16.90 - 34	234	27.00 - 49	612
5.70 - 8	22	27 x 10.00 - 10	53	25 x 12.50 - 15	63	8.25 - 17	48	15.00 - 22.5	106	28.00 - 25	300	24.00 - 25	240	18.50 - 34	260	50 in. Rims	
6.00 - 8	22	27 x 11.00 - 10															