

FOOD GRADE ANTI-SEIZE



LU™ 621



NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145280)



For use in high pressure applications



Maximum Operational Temperature: 1,800 °F (982 °C)



Contains P.T.F.E. (polytetrafluoroethylene)



Military Specification: MIL-A-907E



HMS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- Water & Steam resistant
- Superior leak proof seal
- Effective to 1800 °F
- Meets MIL-A-907E



PRESERVE. PROTECT. PREVENT.®

Sprayon® LU™ 621 Food Grade Anti-Seize is a premium, synthetic, food grade, non-drying thread sealant and anti-seize compound. Formulated with a balanced blend of P.T.F.E. and other lubricating solids, LU™ 621 has been engineered to provide a superior leak-proof seal for the life of the connection while at the same time maintaining its anti-seize capabilities allowing for easy disassembly without thread damage.

LUBRICANTS

FOR USE ON

- Brass, Black Iron, Galvanized Steel, Stainless Steel, Aluminum, Copper, PVC & Fiberglass Reinforced Pipes
- Threaded Fittings • Pins
- Bushings • Valve Shafts
- Flanges • Plugs • Chains
- Manifold Studs & Bolts
- Sprockets • Splines
- Worm Gears • Brake Cams
- Rig Drives • Winches

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU621

APPLICATION

Shake well before using. Do not apply while equipment is running. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to set. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

PLASTIC & RUBBER SAFE: Yes
(Always test before using)
TEMPERATURE RANGE:
HIGH: 1800 °F
LOW: 5 °F
LOAD CAPACITY: High
CORROSION PREVENTION (ASTM D-1743): Pass
WORKED PENETRATION (ASTM D-217)
60 Strokes: 310
10k Strokes: 340

PACKAGING

STOCK #: S00621000
UPC CODE: 0-75577-00625-0
FILL WT.: 15 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE: 800-777-2966
TECHNICAL INFORMATION: 800-251-2486

PROPERTIES

APPEARANCE: White
BASE: Synthetic
FILM TYPE: Grease Like (NLGI 1)
ODOR: Low / Sweet
CONTAINS P.T.F.E: Yes
PROPELLANT: Hydrocarbon Blend
WT./GAL.: 6.22
SPECIFIC GRAVITY: 0.75
% VOC AEROSOL: 64
V.O.C. COMPLIANT CALIFORNIA: Yes
(For use in manufacturing process only)
V.O.C. COMPLIANT OTC STATES: Yes
SARA 313: None
HAPS: None
FLAMMABLE: Yes
FLASH POINT: <0 °F
HAZARD RATING: 2, 3, 0
SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145280



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

Distributed by:

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966