

FOOD GRADE CHAIN LUBRICANT



LU™ 205

	NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145282)
	For use in extreme pressure applications
	Minimum - Maximum operational temperature range: Low 12 °F (-11 °C) • High 450°F (232 °C)
	Meets (OECD) 301B Standards - Rapidly Biodegradable after 301B Standard
	Free of heavy metals such as Barium & Cadmium
	Contains P.T.F.E. (polytetrafluoroethylene)
	HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Extreme pressure lubricity
- Foaming action for deep penetration
- Excellent water resistance and anti-wear properties



PRESERVE. PROTECT. PREVENT.®

Sprayon® LU™205 Food Grade Chain Lubricant is a blend of the finest quality renewable resource oils available, treated with the most effective anti-oxidants, extreme pressure, anti-wear, and corrosion protecting additives. PTFE is added to further enhance load capacity and reduce friction. LU™205 Food Grade Chain Lubricant offers excellent extreme pressure lubricity, water resistance and high temperature performance on chains and much more. Foaming action allows for pin-point application and deep penetration.

LUBRICANTS

FOR USE ON

- Fans • Bearings • Pumps
- Conveyors • Cables
- Electrical Motors • Locks
- Air Tools • Hinges
- Conveyor Chains
- Packaging Equipment
- Hoist Chains
- Link & Roller Assemblies

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU205

APPLICATION

Shake Well Before using. For best results use at room temperature 70°F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

PLASTIC & RUBBER SAFE: Yes (Always test before using)

TEMPERATURE RANGE:

HIGH: 450 °F

LOW: 12 °F

LOAD CAPACITY: Extreme

DIELECTRIC STRENGTH: 46.5 kV

FALEX LOAD (ASTM D-3233A): 3,750 lbs.

4-BALL WEAR SCAR (ASTM D-2266): 0.44 mm

RAPIDLY BIODEGRADABLE (OECD-301): Yes

DELIVERY: SPRAY ANYWAY™ Nozzle

PROPERTIES

APPEARANCE: Light Straw Color

BASE: Bio-based (Vegetable)

FILM TYPE: Wet

ODOR: Low

CONTAINS P.T.F.E: Yes

PROPELLANT: Hydrocarbon Blend

WT./GAL.: 6.86

SPECIFIC GRAVITY: 0.83

% VOC AEROSOL: 15

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

HEAVY METALS: No

FLAMMABLE: Yes

FLASH POINT: <0°F

SARA 313: None

PROP 65: None

HAPS: None

HAZARD RATING: 2, 4, 0

SHELF LIFE: 3 years from date of manufacture

PACKAGING

STOCK #: S00205000

UPC CODE: 0-75577-00618-2

FILL WT.: 15 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: Sprayon.com

CUSTOMER SERVICE:

800-777-2966

TECHNICAL INFORMATION:

800-251-2486

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145282



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

800-777-2966

310-PDS-LU205