



STORM BLASTER®

All Weather Construction Sealant

White Lightning® Storm Blaster is a super-elastomeric sealant that is ideal for exterior use in weather extremes. It can be applied to cold or wet surfaces and still retain its excellent adhesion. White Lightning Storm Blaster can be used on: glass, wood, metal, paint, concrete, asphalt, brick, tile, fiberglass and most plastics.

- Instantly Bonds & Seals – Even Wet and Oily Surfaces
- Permanently Flexible – Won't Crack or Split
- Extreme Temperature Application
- Minimal Surface Prep



WATERPROOF



PAINTABLE



EXTERIOR

PART #	UPC	COLOR	SIZE
W41401010	0-23275-77010-2	Crystal Clear	10 fl. oz.
W41401005	0-23275-00379-8	Crystal Clear	5 fl. oz.
W41000010	0-23275-77515-2	White	10 fl. oz.





STORM BLASTER®

All Weather Construction Sealant

Physical Properties:

Type: Solvent based

Colors: Crystal Clear, White

Shelf Life: 18 Months

Flash Point: 109 °F

Flammability: Combustible

Full Cure Time: 4 days

Tack-Free Time: 2 hours

Application Temperature: 0 °F to 140 °F (-18 °C to 60 °C)

Service Temperature: -40 °F to 180 °F (-40 °C to 82 °C)

Vehicle: Hydrocarbon Solvents

Solids by Weight: 65%

Weight/Gallon: 7.72 lbs/gal

Painting: Paintable

Primers: Not required

Performance Data:

Joint Size: Minimum recommended joint size is 1/4" x 1/4", maximum joint size 1/2" x 1/2" in depth.

Freeze-Thaw Stability: Won't freeze

Shelf Life: 18 Months

Cleanup: Promptly clean up any excess sealant on surface or tools with a regionally compliant cleaning solvent. Wash hands with soap and water.

Flexibility: 1025%

Painting: Latex paint in 24 hours, oil based paint in 3 to 5 days. Allow extra dry time during periods of high humidity and/or cool temperatures.

Application:

1. Surface should be free from loose mortar, release agents, old caulking, old paint or other contaminants.

10 oz. Cartridge

- Cut cartridge tip 45° angle and puncture inner seal.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of sealant and work sealant into joint.
- If needed, tool sealant immediately after application (small amount of soapy water or regionally compliant cleaning solvent helps smoothing)

5 oz. Squeeze Tube

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of sealant and work sealant into joint.
- If needed, too sealant immediately after application (small amount of soapy water or regionally compliant cleaning solvent helps smoothing)

2. Promptly clean up any excess sealant on surface or tools with a regionally compliant cleaning solvent. Wash hands with soap and water.
3. FOR BEST RESULTS: Do not use in areas of continuous submersion (i.e. aquariums or swimming pools). Do not use in areas where temperatures exceed 180 °F. Do not apply to frosty or icy surfaces. STORM BLASTER® may damage some plastics, such as polystyrene foam insulation.

Cleanup:

Promptly clean up any excess sealant on surface or tools with a regionally compliant cleaning solvent. Wash hands with soap and water.

Cautions:

COMBUSTIBLE (during cure). Keep away from heat and open flame. Use only in well-ventilated areas. Avoid contact with eyes and skin. Avoid breathing vapor and spray mist. Wash hands after using. Do not transfer contents to other containers for storage. Keep out of reach of children. **FIRST AID:** In case of eye contact, flush with large amounts of water for at least 15 minutes. Get medical attention. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and laundry before re-use. For inhalation, if affected, remove from exposure. Restore breathing. Keep warm and quiet. If swallowed, do not induce vomiting. Call Poison Control Center, hospital emergency room or physician immediately.

Limitations:

Do not use on traffic-bearing surfaces

- Do not use on extruded polystyrene insulating sheathing (Styrofoam®, etc.)
- Do not use on acrylic skylight glazing surfaces
- Do not use in areas where food is processed or stored
- Do not apply to frozen or frost-covered services.
- Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information, please call or write:

White Lightning Products 101 W Prospect Ave., Cleveland, OH 44115

1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service

wlcaulk.com