

# Bostik® SuperTak™ General Purpose

## Product Description

Bostik® SuperTak™ General Purpose Aerosol Adhesive is a quick tack adhesive especially formulated to bond paper, cardboard, fabric, leather, foil, fiberglass to itself and to metal, wood and a variety of other substrates. It is essentially translucent to pale yellow and produces TEMPORARY OR PERMANENT bonds.

SuperTak™ General Purpose Adhesive is useful in the screen print, pool table and sewing industries.

## Product Benefits

- Spray pattern is a fine mist spray. The valve and tip provides coverage of large areas with a quick uniform coating that offers low soak-in with no staining or wrinkling of lightweight materials. Controlled pattern or fan-type spray tips are available.
- Low soak-in, ideal for low porous surfaces
- Adheres paper, cardboard, fabric, leather, foil, fiberglass to itself and to metal, wood and several other substrates.

## Product Applications

- Bonding fabric and materials for the sewing and pool table industries
- Bonding for screen printing
- Bonding paper, fabric, fiberglass itself and to metal and wood

## Directions for Use

1. Hold the can 6 to 8 inches away from the surface to be sprayed. Depress spray tip (with arrow pointed away from the body) and apply a uniform coating.
2. To clear spray tip, invert can and spray.
3. For porous substrates, applying two coats in the opposite direction of each other will increase bond strength.
4. For permanent bonding applications, apply a heavy coat to both surfaces, let dry for 3 to 5 minutes and press substrates together.
5. For temporary bonds, apply a light coat to one surface only, let dry for 1 minute and bond.
6. Read precautions on label before using.
7. For best results, apply adhesive at temperatures between 50°F (10°C) and 110°F (43°C).

## Available Size

24 FL. OZ., 17 Ounce Net Weight

## Typical Physical Properties\*\* (Not for Specification Use)

Color:	Translucent to Pale Yellow
Base:	Synthetic resin(s) and styrene butadiene copolymer mixture
Solvent System:	Hexane (Aliphatic) and Acetone (Ketone)
Solids:	16.5% ±1.5%
Heat Resistance:	Max. temperature of cured adhesive, 120°F (49°C)
Physical/Chemical Resistance:	Good resistance to oxidation and moisture
Bonding Time:	15 sec. to 2 minutes
Spray Pattern:	Fine particle mist. Valve and tip provides uniform coating, quick coverage of large areas.
Odor:	Mint-like when wet, none when dry
Flammability:	Extremely flammable
Cleanup—Suitable Solvents:	Mineral spirits

## Storage and Handling

Shelf Life:	One year from ship date
Further Information:	Extremely flammable. Keep away from sparks, flame or heat. Please refer to MSDS for complete details.

\*\* Values given above are not intended to be used in specification preparation.

#### **IMPORTANT NOTICE**

All statements, technical information and recommendations set forth herein are based on tests which Bostik believes to be reliable. However, Bostik does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sales of this product shall be on terms and conditions set forth on Bostik's order acknowledgment. Bostik warrants that the product conforms with Bostik written specifications, and is free from defects. BOSTIK DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK BE LIABLE FOR DIRECT, CONSEQUENTIAL ECONOMIC OR OTHER DAMAGES.

**Bostik Findley, Inc.**  
211 Boston Street  
Middleton, MA 01949-2128  
Telephone: 888-603-8558  
[www.bostikfindley-us.com](http://www.bostikfindley-us.com)