

HI 98204

pH/ORP/EC Meter

with °C Temperature Measurement



- 4 instruments in 1
- Long battery life
- Lightweight with built in handle
- Easy to take measurements

Water Test—A Portable Water Testing laboratory

Water Test provides quick and reliable measurement of the four most important variables in water analysis: pH, ORP, conductivity and temperature.

The lightweight and compact body makes it perfect for use in the plant as well as the field. Superior in design and construction, Water Test is made of rugged VALOX® material which provides excellent protection from typical environmental conditions.

Water Test is engineered with such simplicity that even non-technical personnel can use it: fill the base of Water Test with the sample to be measured, press "RANGE" to select the mode and then simply read your measurement!

The rugged construction and simple operation make Water Test perfect for use in the fields of: water treatment analysis, waste water tests, ecological studies, aquaculture and hydroponic applications.

SPECIFICATIONS	PH	ORP	CONDUCTIVITY	TEMPERATURE
Range	0.0 to 14.0 pH	±1000 mV	0 to 1999 µS/cm	0.0 to 60.0°C
Resolution	0.1 pH	1 mV	1 µS/cm	0.1°C
Accuracy (@20°C/68°F)	±0.2 pH	±5 mV	±2% F.S.	±1°C
Calibration	manual, 2 points	factory calibrated	manual, 1 point	factory calibrated
Battery Type / Life	(3) 1.5V / approx. 200 hours of continuous use			
Environment	0 to 50°C (32 to 122°F); RH max 95%			
Dimensions	190 x 85 x 85 mm (7.5 x 3.3 x 3.3")			
Weight	260 g (9.2 oz)			

ORDERING INFORMATION

HI 98204 (Water Test) is supplied with measuring compartment, batteries and instructions.

SOLUTIONS

HI 740088	Plastic vessel for sample	HI 7010M	pH 10.01 buffer solution, 250 mL
HI 7004M	pH 4.01 buffer solution, 250 mL	HI 7020M	200/275 mV test solution, 250 mL
HI 7007M	pH 7.01 buffer solution, 250 mL	HI 7031M	1413 µS/cm calibration solution, 250 mL
		HI 70300M	Electrode storage solution, 250 mL
		HI 7091M	Reducing solution, 250 mL
		HI 7092M	Oxidizing solution, 250 mL

*Carry a Water Test
portable lab anywhere.*

