






pH600/CD600/CD601/CD610/CD611/CD97 pH/EC & TDS Economical Pocket Testers



Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable pH, EC or TDS values.

Measuring electrical conductivity is the best way of checking the amount of salt or dissolved solids (TDS) in water. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions.

All EC/TDS testers compensate for the temperature variance automatically.



Specifications	 pH600	 CD600	 CD601
Range	0.0 to 14.0 pH	0 to 1990 ppm	0 to 1990 µS/cm
Resolution	0.1 pH	10 ppm	10 µS/cm
Accuracy	±0.1 pH	±2% full scale	±2% full scale
Calibration	manual, 1 point		
Temperature Compensation		automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	3 x 1.5V, alkaline / 700 hours of use	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use
Dimensions / Weight	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g

Specifications	 CD610	 CD611	 CD97
Range	0 to 10000 ppm	0 to 20000 µS/cm	0 to 1000 ppm
Resolution	100 ppm	100 µS/cm	1 ppm
Accuracy	±2% full scale	±2% full scale	±10 ppm
Temperature Compensation	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use	4 x 1.5V, alkaline / 350 hours of use
Dimensions / Weight	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g	150 x 30 x 24 mm / 85 g

Accessories

- M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10030B 12880 µS/cm calibration solution, 20 mL (25 pcs)
- M10031B 1413 µS/cm calibration solution, 20 mL (25 pcs)

- M10032B 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)
- M10038B 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)
- M10080B 800 ppm calibration solution 20 mL (25 pcs)
- MA9015 Electrode storage solution, 230 mL
- MA9016 Electrode cleaning solution, 230 mL
- M10000B Electrode rinse solution, 20 mL (25 pcs)



Ordering Information

pH600, CD600, CD601, CD610, CD611 and CD97 are supplied complete with protective cap, calibration screw-driver, batteries and instructions.