

Mi170

Autoranging EC/TDS/NaCl/Temperature Laboratory Bench Meter

Mi170 measures 4 different parameters - EC, TDS (Total Dissolved Solids), percentage of NaCl and temperature in a variety of ranges.

The auto-ranging feature for EC and TDS measurements automatically sets the resolution suitable to the tested sample. All measurements can be temperature compensated at 20 or 25°C and the compensation coefficient is selectable by the user.

The automatic temperature compensation can also be disabled for measuring the actual conductivity value. The stability indicator on the LCD ensures accuracy.

Conductivity readings are performed with the 4-ring probe supplied with the meter. The GLP feature allows users to store and recall data on system status.

PC compatible through an RS232 or USB port.



- Years warranty 3
- LOG
- RS232
- USB
- ATC
- MTT
- Software CD
- Dual Display
- Self diagnostics
- GLP
- CE

Specifications	Mi170
Range	EC 0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm actual conductivity (uncompensated EC)* TDS 0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.5 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L actual TDS* (with 0.80 factor) NaCl 0.0 to 400.0% Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	EC 0.01 µS/cm; 0.1 µS/cm; 1.0 µS/cm; 0.01 mS/cm; 0.1 mS/cm TDS 0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L NaCl 0.1% Temp 0.1°C / 0.1°F
Accuracy	EC ±1% of reading ±(0.05 µS/cm or 1 digit) TDS ±1% of reading ±(0.03 mg/L or 1 digit) NaCl ±1% of reading Temp ±0.4°C / ±0.8°F
Calibration	EC 1 point slope calibration with 6 memorized solutions (84.0 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm) NaCl 1 point, with MA9066 calibration solution Temp 2 points, 0 to 50°C / 32 to 12 °F
Temp. Compensation	automatic or manual, from -20.0 to 120.0°C / -4.0 to 248.0°F
Temp. Coefficient	selectable from 0.00 to 6.00%/°C (EC and TDS only)
Probe	MA814DB/1 4-ring probe with built-in temperature sensor (included)
TDS Factor	0.40 to 0.80 (default value is 0.50)
Log on Demand	up to 50 samples on each range (EC, TDS, NaCl)
GLP	last EC, NaCl calibration data
PC Interface	RS232 / USB Opto-isolated
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Power supply	12 VDC power adapter (included)
Dimensions	230 x 160 x 95 mm
Weight	0.9 kg

(*) Uncompensated conductivity (or TDS) is the conductivity (or TDS) value without temperature compensation.

More accurate readings with the 4-RING MA814DB/1 EC/TDS and Temperature probe!

Conductivity readings are performed by applying an alternate current to the 4-ring probe which creates a variable voltage depending on the conductivity.



Rear Connector Panel layout

Communication to the PC is done via opto-isolated USB and RS232 ports.



Accessories

- MA814DB/1 EC/Temperature probe with DIN connector and 1 m cable
- MA9060 12880 µS/cm calibration solution, 230 mL bottle
- MA9061 1413 µS/cm calibration solution, 230 mL bottle
- MA9063 84 µS/cm calibration solution, 230 mL bottle
- MA9064 80000 µS/cm conductivity solution, 230 mL bottle
- MA9065 111.8 mS/cm calibration solution, 230 mL bottle



- MA9066 100% NaCl calibration solution, 230 mL bottle
- MA9069 5000 µS/cm solution, 230 mL bottle
- MA9310 12 VDC Adapter, 220 V
- MA9311 12 VDC Adapter, 110 V
- MA9315 Electrode holder
- MA9350 RS232 connection cable with 2 meters cable
- Mi5200 Application Software

Ordering Information

- Mi170 is supplied complete with
- MA814DB/1 EC/TDS/Temperature Probe
 - MA9315 Electrode Holder
 - M10030 12880 µS/cm calibration solution
 - M10031 1413 µS/cm calibration solution
 - Mi5200 Application Software
 - MA9350 RS232 connection cable with 2 meters cable
 - 12 VDC Adapter
 - Instruction manual