

PULSAtron®

Series E PLUS

Electronic Metering Pumps



Key Features

- **Automatic Control**, available with 4-20 mADC direct or external pacing, with stop function.
- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Flow Verification** option is available on select sizes.
- **Auto-Off-Manual** switch.
- **Highly Reliable** timing circuit.
- **Circuit Protection** against voltage and current upsets.
- **Panel Mounted Fuse**.
- **Solenoid Protection** by thermal overload with auto-reset.
- **Water Resistant**, for outdoor and indoor applications.
- **Indicator Lights**, panel mounted.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).

Complete Economical Selection

Nineteen distinct models are available, having pressure capabilities to 300 PSIG @ 3 GPD, and flow capacities to 504 GPD @ 20PSIG, with a turndown ratio of 100:1. Metering performance is reproducible to within $\pm 2\%$ of maximum capacity.

Please refer to the reverse side for Series E PLUS specifications.

Operating Benefits

Reliable metering performance. Our guided check valves, with their state-of-the-art seat and ball designs, provide precise seating, and excellent priming and suction lift characteristics. Our timing circuit is highly reliable and, by design, virtually unaffected by temperature, EMI and other electrical disturbances.

Rated "hot" for continuous duty. Series E PLUS pumps continue to meet their specifications for pressure and capacity even during extended use. That's because of our high quality solenoid and special enclosure that effectively dissipates heat.

High viscosity capability. A straight flow path and ample clearance between the diaphragm and head enable standard PULSAtron pumps to handle viscous chemicals up to a viscosity of 3000 CPS. For higher viscosity applications, larger, spring-loaded connections are available.

Flow Verification. Equipped pumps utilize an "In Line" flow monitor to automatically disable the pump and activate an alarm relay should the pump flow be interrupted.

System Compatibility

A wide variety of chemicals can be pumped.

Liquid end materials include glass-filled polypropylene (GFPP), PVC, styrene-acrylonitrile (SAN), Polyvinylidene Fluoride (PVDF), PTFE, Hypalon, Viton, ceramic, alloys and 316SS.

Immediate installation and start-up.

Included as standard accessories with all models are an injection/back pressure valve assembly and a foot valve/strainer assembly*, including discharge and suction tubing (*not avail. with high viscosity connections for >3000 CPS).

Safe and easy priming and valve maintenance.

Included as a standard accessory is a bleed valve assembly, including return tubing (available only on those models with tubing connections and ≤ 240 GPD).

Quick and economical liquid end maintenance.

Available for every model is a unique KOPkit®, a convenient, economically priced, package containing new cartridge check valves and other important spare parts.



Agency approved for demanding **OUTDOOR** and indoor applications.

For additional information about PULSAtron's full-featured Series MP refer to Technical Sheet No. EMP-027, about the mid-range Series E, Series D & Series A PLUS refer to Technical Sheet No. EMP-022, EMP-023 & EMP-025. For information about the economical Series C PLUS & Series C, refer to Technical Sheet No. EMP-026 & EMP-024.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



technology
innovation
diversity
excellence

PULSAtron Series E PLUS Specifications

Pressure and Flow Rate Capacity

MODEL		LPK2	LPB2	LPA2	LPD3	LPB3	LPA3	LPK3	LPF4	LPD4	LPB4	LPH4	LPG4	LPE4	LPK5	LPH5	LPH6	LPK7	LPH7	LPH8
Capacity	GPH	0.13	0.21	0.25	0.50	0.50	0.50	0.60	0.85	0.90	1.00	1.70	1.75	1.85	2.50	3.15	5.00	8.00	10.00	25.00
nominal	GPD	3	5	6	12	12	12	14	20	22	24	41	42	44	60	76	120	192	240	600
(max.)	LPH	0.5	0.8	0.9	1.9	1.9	1.9	2.3	3.2	3.4	3.8	6.4	6.6	7.0	9.5	11.9	18.9	30.3	37.9	94.6
Pressure	PSIG	300	250	150	250	150	100	100	250	150	100	250	150	100	150	150	100	50	35	30
(max.)	BAR	21	17	10	17	10	7	7	17	10	7	17	10	7	10	10	7	3.3	2.4	2
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD 1/4" FNPT													3/8" ID X 1/2" OD 1/2" ID x 3/4" OD (LPH8 ONLY) FLOW VERIFICATION (See Note) 1/4" FNPT 1/2" FNPT					
	Piping																			
Reproducibility at max. capacity		+/- 2%																		
Viscosity Max CPS		For viscosity up to 3000 CPS, select connection size 3, 4, B or C with 316SS ball material. Flow rate will determine connection/ball size. Greater than 3000 CPS require spring loaded ball checks. See Selection Guide for proper connection.																		
Stroke Frequency Max SPM		125																		
Stroke Frequency Turn-Down Ratio		10:1																		
Stroke Length Turn-Down Ratio		10:1																		
Power Input		115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph																		
Average Current Draw @ 115 VAC: Amps @ 230 VAC: Amps		1.0 0.5																		
Peak Input Power Watts		300																		
Average Input Power @ max SPM: Watts		130																		

Important: Series E PLUS - 19 model selections. Digit 1 and 2 (LP) signify product class, digit 3 and 4 signify pressure/flow. For full model selection information refer to Price Schedule EMP-PS LP.



Flow Verification: Available on K3, B4 and E4 with connection code 1; H6, K7 and H7 with connection code H; 1/4" ID x 3/8" OD only.

Liquid End Materials

Series	Pump Head	Diaphragm	Check Valves		Fittings	Bleed Valve	Injection Valve Assembly Foot Valve Assembly	Tubing
			Seats / O-Rings	Balls				
E PLUS	GFPPL PVC SAN PVDF 316 SS	PTFE-faced Hypalon-backed	PTFE, Hypalon, Viton	Ceramic, PTFE, 316SS, Alloy C	GFPPL PVC PVDF	Same as fitting and check valve selected, except 316SS	Same as fitting and check valve selected	Clear PVC White PE

Important: Material Code— GFPPL = Glass-filled Polypropylene, PVC = Polyvinyl Chloride, SAN = Styrene-Acrylonitrile, PE = Polyethylene, PVDF = Polyvinylidene Fluoride. Hypalon and Viton are registered trademarks of E.I. DuPont Company. PVC wetted end recommended for sodium hypochlorite.

Dimensions



Series E Plus Dimensions (inches)																	
Model No.	A	B	B1	C	C1	D	E	Shipping Weight	Model No.	A	B	B1	C	C1	D	E	Shipping Weight
LPA2	5.4	10.3	-	10.8	-	7.5	8.9	13	LPH4	6.2	10.9	-	11.2	-	8.2	9.5	21
LPA3	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH5	6.2	11.3	-	11.2	-	8.2	9.9	21
LPB2	5.4	10.3	-	10.8	-	7.5	8.9	13	LPH6	6.2	11.3	-	11.9	-	8.2	9.9	21
LPB3	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH7	6.1	11.7	-	11.9	-	8.2	10.3	21
LPB4	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH8*	6.1	-	10.9	-	11.3	8.2	-	26
LPD3	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK2	5.4	10.3	-	10.8	-	7.5	8.9	13
LPD4	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK3	5.4	10.6	-	10.7	-	7.5	9.2	13
LPE4	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK5	5.4	10.9	-	11.7	-	7.5	9.5	18
LPF4	5.4	10.6	-	11.7	-	7.5	9.2	18	LPK7	6.1	11.7	-	11.2	-	8.2	10.3	21
LPG4	5.4	10.6	-	11.7	-	7.5	9.2	18									

NOTE: Inches X 2.54 = cm
* the LPH8 is designed without a bleed valve available.



An ISO Certified Company



Brochure No. EMP-021
Printed in the USA D08



A Unit of IDEX Corporation

Standard Product Operations
27101 Airport Road • Punta Gorda, Florida 33982
TEL (941) 575-3800 • TEL 800-333-6677
FAX (941) 575-4085 • FAX 800-456-4085
spotech@pulsa.com • www.pulsa.com