

# MAINTENANCE MADE EASY



Superior Products & Support for the Swimming Pool & Spa Service Professional

**ROLA-CHEM™**

Rola-Chem.com | 800-549-4473

MAINTENANCE MADE EASY

ROLA-CHEM™

A PREFERRED CHOICE OF COMMERCIAL POOL AND  
SPA MAINTENANCE PROFESSIONALS SINCE 1964



**Your Customers Want One Thing: The Perfect Pool**

At Rola-Chem, helping pool maintenance professionals achieve the Perfect Pool is in our DNA. From precise chemical feeding to advanced control and monitoring, our products are engineered for optimal efficiency and ease-of-use. We understand that water quality systems that are easier-to-use and consistent will help you exceed customer's expectations, grow your business and increase profit.

## ROLA-CHEM IS MAINTENANCE MADE EASY

Our goal is to make maintenance easier for pool and spa service professionals. We are your trusted source for reliable equipment that will save you time and money and allow your customers to spend more time enjoying their investment.

### Pool Professionals Tell Us That Maintenance is Made Easier...

- When system equipment is intuitive and works
- When system components needed can be sourced from one company, ordered with a single part number and trained professionals are available via call or online chat
- When complete systems can be easily installed and set up right from the box
- When set up can be achieved without manuals
- When little technical expertise is needed
- When troubleshooting and support videos are hosted on YouTube
- When all you need is the electrical, tanks, and space to hang a fully integrated, Ready-to-Mount System—no complicated instructions
- When your customer can spend 60% less time monitoring and managing pool and spa water quality then with other methods



## A LEGACY OF INNOVATION

For over fifty years Rola-Chem has relied on the expertise and best practices of certified pool service professionals to achieve the perfect pool. From large pool service companies to small owner-operated businesses, the Rola-Chem brand has remained true to its roots and remains focused solely on pool water quality systems in both commercial and residential installations. At the core of our success is the reliable Rola-Chem peristaltic pump. While the basic function of our pump/controller systems remains the same (programmed chemical dosing and monitoring), our products have evolved as technology has advanced. Our ability to provide consistent improvements to our systems would not be possible without feedback from you, the Pool Service Pro.



*"Because Rola-Chem is so reliable and easy-to-use, I can serve more customers and make more money."*

**Hector Munoz—HDM Pools**

**WARNING:** This product can expose you to chemicals including Carbon Black which is known to the state of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

## WHAT'S NEW?

This catalog presents several new ways that Maintenance is Made Easy by Rola-Chem:

- The New PRO Series 300 Feeder
- 5 new Ready-to-Mount Systems
- Links to Installation and How-to videos



Pool Pros Coast to Coast—Pro tips to simplify your Job

## TABLE OF CONTENTS

Peristaltic Pumps Pro Series 300 .....	3
Peristaltic Pumps Pro Series .....	4
Digital Controllers .....	5-6
Ready-to-Mount Systems .....	7-9
Control Systems Diagrams .....	10
Professional System Components .....	11-12
Flow Meters .....	13
Chemical Tanks .....	14



Maintenance is made easier with our YouTube video library. From installation and set-up to trouble shooting, help with Rola-Chem equipment is a click away.

[youtube.com/user/inforolachem](https://youtube.com/user/inforolachem)

## **NEW!** THE PRO SERIES 300 PERISTALTIC PUMPS

The **NEW PRO Series 300 Peristaltic Pumps** maintain the best of the Rola-Chem Pro Series legacy\* while improving primary function and simplifying set up.



**MODEL SHOWN :**  
**RC305MC**  
P/N 543818  
UPC 7-57706 00038-3

Three-Roller Operation



\*Mounting patterns and many parts interchange with legacy Pro Series models.



**MODEL SHOWN:**  
**RC301MC**  
P/N 543807  
UPC 7-57706 00027-7

Two-Roller Operation  
(1) GPD Pump Only



ALL ROLA-CHEM PUMPS ARE   LISTED

**ESTIMATED FEED RATES**  
AT GIVEN TIMER SETTINGS – GALLONS PER DAY

SETTING %	ON TIME	OFF TIME	RC301	RC303	RC305	RC307
1	5.4 SEC	8.9 MIN	—	0.12	0.38	0.77
2	10.8 SEC	8.8 MIN	0.02	0.24	0.76	1.54
3	16.2 SEC	8.7 MIN	0.03	0.36	1.14	2.31
4	21.6 SEC	8.6 MIN	0.04	0.48	1.52	3.08
5	27.0 SEC	8.6 MIN	0.05	0.60	1.90	3.85
6	32.4 SEC	8.5 MIN	0.05	0.72	2.28	4.62
7	37.8 SEC	8.4 MIN	0.06	0.84	2.66	5.39
8	43.2 SEC	8.3 MIN	0.07	0.96	3.04	6.16
9	48.6 SEC	8.2 MIN	0.08	1.08	3.42	6.93
10	54.0 SEC	8.1 MIN	0.09	1.20	3.80	7.70
15	1.4 MIN	7.7 MIN	0.14	1.80	5.70	11.55
20	1.8 MIN	7.2 MIN	0.18	2.40	7.60	15.40
25	2.3 MIN	6.8 MIN	0.23	3.00	9.50	19.25
30	2.7 MIN	6.3 MIN	0.27	3.60	11.40	23.10
35	3.2 MIN	5.9 MIN	0.32	4.20	13.30	26.95
40	3.6 MIN	5.4 MIN	0.36	4.80	15.20	30.80
45	4.1 MIN	5.0 MIN	0.41	5.40	17.10	34.65
50	4.5 MIN	4.5 MIN	0.45	6.00	19.00	38.50
55	5.0 MIN	4.1 MIN	0.50	6.60	20.90	42.35
60	5.4 MIN	3.6 MIN	0.54	7.20	22.80	46.20
65	5.9 MIN	3.2 MIN	0.59	7.80	24.70	50.05
70	6.3 MIN	2.7 MIN	0.63	8.40	26.60	53.90
75	6.8 MIN	2.3 MIN	0.68	9.00	28.50	57.75
80	7.2 MIN	1.8 MIN	0.72	9.60	30.40	61.60
85	7.7 MIN	1.4 MIN	0.77	10.20	32.30	65.45
90	8.1 MIN	54.0 SEC	0.81	10.80	34.20	69.30
95	8.6 MIN	27.0 SEC	0.86	11.40	36.10	73.15
99	8.9 MIN	5.4 SEC	0.89	11.88	37.62	76.23
On	CONTINUOUS		0.90	12.00	38.00	77.0

### The Pro Series 300 Features:

- New commercial design
- Fully digital timer
- Refined dosing increments— for more precise control
- New, more versatile mounting options
- Other features include: quick-release cover for fast tubing access, three-way switch controls timer/off/continuous, self-priming pump and clear Tygon and Black Norprene Squeeze Tubes
- The Pro Series 300 retains a 30psi rating and versatile 18-ft. suction lift.
- Pumps operate on 9-minute cycles and are available in 120V or 240V corded or permanent wire configurations with maximum amps—2.5

SEE [ROLA-CHEM.COM](http://ROLA-CHEM.COM) FOR THE COMPLETE LIST OF PRO SERIES 300 MODELS

## PRO SERIES PERISTALTIC PUMPS

Rola-Chem peristaltic pumps deliver professional quality features that simplify operation and maintenance.



**MODEL SHOWN:  
RC103SC**  
P/N 543702  
7-57706 00007-9



**MODEL SHOWN:  
RC252SC**  
P/N 543709  
UPC 7-57706 00012-3

ALL ROLA-CHEM PUMPS ARE  LISTED

### ROLA-CHEM PRO SERIES SIZING GUIDE

ESTIMATED MAXIMUM GALLONS PER DAY

SETTINGS	ON	OFF	RC-252	RC-25/53	RC-103	RC-503
LO	4 SEC.	8 MIN. 56 SEC.	.01	.10	.34	1.00
2	1.5 MIN.	7.5 MIN.	.18	1.20	3.72	8.88
3	3 MIN.	6 MIN.	.33	3.60	10.80	24.00
4	4.5 MIN.	4.5 MIN.	.50	6.00	19.40	40.00
5	6 MIN.	3 MIN.	.66	8.40	25.20	53.00
6	7.5 MIN.	1.5 MIN.	.78	11.00	33.40	67.00
HI	8 MIN. 56 SEC.	4 SEC.	.90	12.00	38.00	77.00
<b>OUNCES PER MINUTE AT FULL ON</b>			.08	1.06	3.37	6.84

### ROLA-CHEM PRO SERIES OUTPUT

PRO SERIES 300 MODEL	LEGACY SERIES MODEL	MINIMUM FEED RATE/24HR	MAXIMUM FEED RATE/24HR	RECOMMENDED VOLUME OF SPA WATER TO BE TREATED (GALLONS)*	RECOMMENDED VOLUME OF POOL WATER TO BE TREATED (GALLONS)*	MAX. VOLUME OF WATER TO BE TREATED (GALLONS) - PER CALIFORNIA BUILDING CODE TITLE 24
RC-301	RC-252 SC	.01 GPD	.9 GPD	500-2,500	2,500-5,000	3,000
RC-303	RC-25/53 SC	.12 GPD	12 GPD	2,500-25,000	5,000-65,000	40,000
RC-305	RC-103 SC	.38 GPD	38 GPD	-	65,000-200,000	127,000
RC-307	RC-503 SC	.75 GPD	77 GPD	-	180,000-400,000	257,000

GPD = GALLONS PER DAY \*USING 12.5% LIQUID CHLORINE

## GENERATION II DIGITAL CONTROLLERS



**MODEL SHOWN: RC554XP**  
**Digital pH/ORP Controller**

P/N 554000  
 UPC 7-57706 00136-6

	pH	ORP	Feed Cycle
Factory Setting	7.4	650 mV	.6 Seconds
Display Range	6.8–8.2	0–995 mV	
Setpoint Range	7.0–8.0	400–900 mV	

Feed Cycles	.6 to 900 seconds w/ 5-minute analyzation periods
Power	120V corded (input/output)
Feed	Timed or Continuous
Maximum Output	5 Amps

**INCLUDES:** Controller, flow cell with flow switch, probes, 3/8" tubing and fittings.

ALL ROLA-CHEM CONTROLLERS ARE  NSF ANSI CERTIFIED



**MODEL SHOWN: RC554XXP**  
**Digital pH/Dual ORP Controller**

Used to Control Two Sanitizer Sources

P/N 554300  
 UPC 7-5770 600143-4

	pH	ORP 1	ORP 2	Feed Cycle
Factory Setting	7.4	650 mV	640 mV	.6 Seconds
Display Range	6.8–8.2	0–995 mV	0–995 mV	
Setpoint Range	7.0–8.0	400–900 mV	400–900 mV	

Feed Cycles	.6 to 900 seconds w/ 5-minute analyzation periods
Power	120V corded (input/output)
Feed	Timed or Continuous
Maximum Output	3.15 Amps

**INCLUDES:** Controller, flow cell with flow switch, probes, 3/8" tubing and fittings.

### Digital pH/ORP Controllers Feature:

- Digital readouts
- ORP technology
- Redox sensor
- Dip switch programmable settings
- Timed or continuous feed settings
- Built-in out-of-range safety timeouts
- pH calibration
- Acid or base feed
- Microprocessor logic
- Globe flow cell with flow switch
- Compatible with most peristaltic pumps
- Can also be used with erosion feeder/solenoid applications

**MANUFACTURED IN THE USA**

5-YEAR LIMITED WARRANTY ON CONTROLLER ELECTRONICS. 1-YEAR LIMITED WARRANTY ON PROBES, FLOW CELL AND VALVE.

NOTE: It is recommended that an in-line filter system (part number 550591) be used before the flow cell. MET controllers are also available.



**MODEL SHOWN:  
RC554P**

**Digital pH  
Controller**

P/N 554200  
UPC 7-57706 00140-3

- Easy to read, sun bright LED display
- Compact package (approx. 7" x 3" x 3")

**MANUFACTURED  
IN THE USA**

	pH	Feed Cycle
Factory Setting	7.4	.6 Seconds
Display Range	6.8–8.2	
Setpoint Range	7.0–8.0	

Feed Cycles	.6 to 900 seconds w/ 5-minute analyzation periods
Power	120V corded (input/output)
Feed	Timed or Continuous
Maximum Output	5 Amps

**INCLUDES:** Controller, flow cell with flow switch, PH probe, 3/8" tubing and fittings.



**MODEL SHOWN:  
RC554X**

**Digital ORP  
Controller**

P/N 554230  
UPC 7-57706 00142-7

- Easy to read, sun bright LED display
- Compact package (approx. 7" x 3" x 3")

**MANUFACTURED  
IN THE USA**

	ORP	Feed Cycle
Factory Setting	650 mV	.6 Seconds
Display Range	0–955 mV	
Setpoint Range	400–900 mV	

Feed Cycles	.6 to 900 seconds w/ 5-minute analyzation periods
Power	120V corded (input/output)
Feed	Timed or Continuous
Maximum Output	5 Amps

**INCLUDES:** Controller, flow cell with flow switch, ORP probe, 3/8" tubing and fittings.

ALL ROLA-CHEM CONTROLLERS ARE  NSF ANSI CERTIFIED



**MODEL RC554M  
Controller Remote Monitor**

P/N 554400  
UPC 7-57706 00147-2

- Monitor is compatible with Rola-Chem Generation II Digital pH/ORP Controllers: RC554XP (manufactured after October 2015) and RC554XXP (manufactured after May 2016)
- Monitor will upload controller data at specific intervals that are set by operator


- Secure website with operator set password
- Serial connection cable from monitor to data port of controller is included
- A hardwired ethernet connection with unrestricted internet access must be available
- LED lights verify connection to local network (Green) and activity (Amber)
- Internal reset button—used to reconnect monitor to server
- Power down will automatically reconnect monitor to server
- No subscription required

**5-YEAR LIMITED WARRANTY ON CONTROLLER ELECTRONICS. 1-YEAR LIMITED WARRANTY ON PROBES, FLOW CELL AND VALVE.**  
NOTE: It is recommended that an in-line filter system (part number 550591) be used before the flow cell.



*"After setting up my first Rola-Chem Remote Monitor, I received an alert from the web-based system that prompted a call to my resort customer to check on it. He told me it was a "low flow signal" he was able to quickly correct, I was relieved and the alert saved me a long drive to trouble shoot the problem. I saved time, my customer saved money."*

**John Sims—Commercial Pool Supply**



## **NEW!** PRO SERIES 300 READY-TO-MOUNT SYSTEMS

ALL COMPONENTS REQUIRED FOR POOL AUTOMATION MOUNTED ON A POLYPROPYLENE BOARD

Easy Set-up, Reliable Dosing, Trusted—All in One System

Pool professionals have told us our Ready-to-Mount systems take the hassle out of installing and maintaining water chemistry control. Each of the Ready-to-Mount configurations include: fully integrated, board mounted pump(s), controller and monitoring components that are literally plug and play. And the best part is—each system can be ordered with one part number and one PO. All you need is a supply tank and electricity. You and your customer are on their way to the Perfect Pool faster than ever.

**MODEL SHOWN: 554500**

UPC 7-57706 00116-8

### pH Liquid Acid/ORP Liquid Chlorine System

**INCLUDES:** Programmable Digital pH/ORP Controller complete with Flow Cell, Flow Switch, Sample Valves, ORP and pH Probes, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, two Pro Series 300 Peristaltic Pumps (38 GPD), In-line Flow Cell Strainer.

**Also Available:**

**554501** UPC 7-57706 00117-5  
Includes one **38 GPD** & one **12 GPD** Peristaltic Pump

**554502** UPC 7-57706 00118-2  
Includes two **1 GPD** Peristaltic Pumps

**554503** UPC 7-57706 00119-9  
Includes two **12 GPD** Peristaltic Pumps

**554504** UPC 7-57706 00120-5  
Includes one **1 GPD** & one **12 GPD** Peristaltic Pump

**554508** UPC 7-57706 00123-6  
Includes two **77 GPD** Peristaltic Pumps

**554512** UPC 7-57706 00126-7  
Includes one **77 GPD** & one **38 GPD** Peristaltic Pump



**MODEL SHOWN: 554518**

UPC 7-57706 00131-1

### Control Two Sanitizer Sources with Digital pH/Dual ORP System

**INCLUDES:** Programmable Digital pH/Dual ORP Controller complete with Flow Cell, Flow Switch, Sample Valves, ORP and pH Probes, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, two Peristaltic Pumps (38 GPD), In-line Flow Cell Strainer.

**Also Available:**

**554519** UPC 7-57706 00132-8  
Includes one **38 GPD** Peristaltic Pump and one Solenoid Kit

**554520** UPC 7-57706 00133-5  
Includes one **38 GPD** Peristaltic Pump & one **12 GPD** Peristaltic Pump

**554521** UPC 7-57706 00134-2  
Includes one **12 GPD** and one **Solenoid Kit**

**554522** UPC 7-57706 00135-9  
Includes two **12 GPD** Peristaltic Pumps



**NEW!**

## READY-TO-MOUNT CONTROLLER SYSTEMS

ALL COMPONENTS REQUIRED FOR POOL AUTOMATION MOUNTED ON A POLYPROPYLENE BOARD

**MODEL SHOWN: 554510**

UPC 7-57706 00124-3

### pH/ORP Erosion Feeder System

**INCLUDES:** Programmable Digital pH/ORP Controller complete with Flow Cell, Flow Switch, Sample Valves, ORP and pH Probes, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, one Peristaltic Pump (38 GPD), 120 volt Solenoid Kit (includes Solenoid, In-line filter and Check Valve), In-line Flow Cell Strainer.

*Erosion Feeder NOT included.*

**Also Available:**

**554505** UPC 7-57706 00121-2

Includes one **12 GPD** Peristaltic Pump and one Solenoid Kit

**550290**

UPC 7-57706

00240-0

### Solenoid Kit

Rola-Chem Solenoid Kit

550290 is rated for a maximum pressure differential of 6 psi and has a valve coefficient (Cv) of 2. Some erosion feeders require a solenoid rated for higher flow. Contact the manufacturer for requirements.



**MODEL 554511**

UPC 7-57706 00125-0

### pH/ORP Salt Generator System

**INCLUDES:** Programmable Digital pH/ORP Controller complete with Flow Cell, Flow Switch, Sample Valves, ORP and pH Probes, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, one Peristaltic Pump (38 GPD), In-line Flow Cell Strainer.

*Power output to Salt Generator (not included) is 110 Volt 5 Amp*

**Also Available:**

**554506** UPC 7-57706 00122-9

Includes one **12 GPD** Peristaltic Pump



*"A Rola-Chem Ready-To-Mount system installation requires very little technical expertise. Most customers can be guided on system set up questions over the phone I can't say that about any other manufacturer's system."*

**Mike Volkers, CFP—Horizon Pool Supply**



**NEW!**

## READY-TO-MOUNT CONTROLLER SYSTEMS

ALL COMPONENTS REQUIRED FOR POOL AUTOMATION MOUNTED ON A POLYPROPYLENE BOARD

**MODEL SHOWN: 554513**

UPC 7-57706 00127-4

### pH Only Liquid Acid System

**INCLUDES:** Programmable Digital pH Controller complete with Flow Cell, Flow Switch, Sample Valves, pH Probe, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, one Peristaltic Pump (38 GPD), In-line Flow Cell Strainer.

**Also Available:**

**554514** UPC 7-57706 00128-1

includes one **12 GPD** Peristaltic Pump



**MODEL SHOWN: 554516**

UPC 7-57706 00129-8

### ORP Only Liquid Chlorine System

**INCLUDES:** Programmable Digital ORP Controller complete with Flow Cell, Flow Switch, Sample Valves, ORP Probe, 40' of Black 3/8" Tubing, 100' Clear 7/16" Tubing and Fittings, one Peristaltic Pump (38 GPD), In-line Flow Cell Strainer.

**Also Available:**

**554229** UPC 7-57706 00106-9

Includes one 120 volt Solenoid Kit (for Erosion System)


**554517** UPC 7-57706 00130-4

Includes one 12 GPD Peristaltic Pump



[youtube.com/user/inforolachem](https://youtube.com/user/inforolachem)


## Liquid System



\*Flow switch to ensure circulation to control probes and indication that pool circulation is occurring (included in Digital Controller/Globe Flow Cell Only)

\*\*Safety flow Switch for protection of heater and to ensure dilution of chemical into the pool

## Erosion System



\*Flow switch to ensure circulation to control probes and indication that pool circulation is occurring (included in Digital Controller/Globe Flow Cell Only)

\*\*Safety flow Switch for protection of heater and to ensure dilution of chemical into the pool

Rola-Chem Solenoid Kit 550290 is rated for a maximum pressure differential of 6 psi and has a valve coefficient of (Cv) 2.  
Some erosion feeders require a solenoid rated for a higher flow. Contact the manufacturer for requirements.

## PROFESSIONAL SYSTEM COMPONENTS



**550290 Solenoid Kit**

Rola-Chem Solenoid Kit 550290 is rated for a maximum pressure differential of 6 psi and has a variation coefficient (Cv) of 2. Some erosion feeders require a solenoid rated for higher flow. Contact the manufacturer for requirements.



**550180 Globe Flow Cell**

Made from high-impact acrylic with Flow Switch

- For Digital Controller Systems



**550089 Probe Replacement Fitting**

- For Flow Cells



**550135 8' pH Heavy-Duty Probe**

**550208 3' pH Heavy-Duty Probe**



**550136 8' ORP Heavy-Duty Probe**

**550209 3' ORP Heavy-Duty Probe**

- For Digital & Analog Controller System



**7125190 Quick Connect Valve**


3/8" Tubing x 1/4" MNPT

- For Flow Cells



**550193 Tubing Connectors**

3/8" Tubing x 1/4" MNPT



**550201 ORP Gold Tip Probe**

- Recommended for use with Chlorine (Salt) Generators



**550194 Black Tubing**

3/8"





*"My customers rely on their Rola-Chem's because they just work!"*

**Joe Dettrey—  
Commercial Pool Supplies**




[youtube.com/user/inforolachem](https://www.youtube.com/user/inforolachem)

## PROFESSIONAL SYSTEM COMPONENTS



## NO MORE CLOGGED FLOWMETERS!

ROLA-CHEM'S FLOWMETERS HAVE A WIDE CHAMBER THAT GREATLY REDUCES MINERAL DEPOSITS BY ALLOWING HIGHER FLOW VOLUME



Designed to be compatible with practically every existing flowmeter, replace your old clogged flowmeters with these accurate, easily serviced units from Rola-Chem.

Rola-Chem flowmeters are built to withstand water temperatures up to 200°F and are manufactured to work with schedule 40 PVC pipe.

### ACCURATE READINGS

- Our heavy-duty gasket ensures airtight seals

### VISUAL INDICATOR

- Calibrated on both sides in gallons and liters per minute

### SERVICEABLE

- Easily open and remove calcium deposits if necessary

### FULL RANGE MOUNTING

- Side, vertical, or top 1" to 8"; please specify when ordering. Vertical mount is reversible for up or down reading.
- Requires 3/4" diameter hole in pipe

### EASY-TO-READ BOBBIN

- 316 stainless steel ball prevents corrosion

### Easy-to-Use Vertical Mount Gaskets for Nine PVC Pipe Sizes



### FLOW METER SIZING GUIDE

MODEL NO.	PIPE MATERIAL	PIPE SIZE	A* MINIMUM	B* MINIMUM	RANGE GPM	RANGE LPM	CLAMP SIZE
570321	PVC-GALV	1"	5"	10"	10-30	38-114	40
570331	PVC-GALV	1.25"	6"	11"	15-50	57-189	44
570340	COPPER	1.5"	8"	15"	20-55	76-208	44
570341	PVC-GALV	1.5"	8"	15"	25-60	95-227	44
570350	COPPER	2"	10"	20"	40-140	151-530	56
570351	PVC-GALV	2"	10"	20"	40-140	151-530	56
570360	COPPER	2.5"	13"	25"	70-245	265-927	64
570361	PVC-GALV	2.5"	13"	25"	70-240	265-908	64
570370	COPPER	3"	15"	30"	100-280	379-1060	64
570371	PVC-GALV	3"	15"	30"	100-300	379-1136	64
570380	COPPER	4"	20"	40"	200-480	757-1816	44 (2)
570381	PVC-GALV	4"	20"	40"	175-500	662-1893	44 (2)
570391	PVC-GALV	6"	30"	60"	400-1050	1514-3975	64 (2)
570401	PVC-GALV	8"	40"	80"	700-1900	2650-7192	72 (2)

\*A = Minimum distance from downstream elbow or restriction. \*\*B = Minimum distance from upstream elbow or restriction.  
After Part Number, Indicate Mounting: (T) = Top • (S) = Side • (V) = Vertical



## CHEMICAL TANKS

Rola-Chem offers a range of heavy duty tanks and covers available in 5, 15, 30, and 55 gallon sizes. Precision mold- ed of high-density polyethylene polymer, which is highly resistant to corrosive solutions.

### Chemical Tanks Feature:

- Heavy Duty Construction—formed from high-density polyethylene
- Translucent - allows visual check of chemical level
- UV Protected - solar rays will not damage chemicals

PART NO.	PRODUCT DESCRIPTION	CAPACITY	HT.	DIA.	WT.
561405	Tank/Cover/Plug - 5 Gallon	5 Gallon	15.5"	15"	6#
561415	Tank/Cover/Plug - 15 Gallon	15 Gallon	23"	17"	15#
561430	Tank/Cover/Plug - 30 Gallon	30 Gallon	30"	20"	17#
561455	Tank/Cover/Plug - 55 Gallon	55 Gallon	38"	27"	22#
561265	System Tank*	15 Gallon	36.75"	15"	12#



## SYSTEM TANK

### System Tanks Feature:

- Convenient mounting of your Rola-Chem Pump on tank
- Includes chemical refill and pick-up holes
- Heavy Duty Construction—formed from high-density polyethylene
- Translucent—allows visual check of chemical level
- UV Protected—solar rays will not damage chemicals

**543853** UPC 7-57706 00281-3

RC305 MC Rola-Chem Pro Series 300 Pump 120 volt 38 GPD mounted on a 15-Gallon Poly Tank

**543854** UPC 7-57706 00282-0

RC303 MC Rola-Chem Pro Series 300 Pump 120 volt 12 GPD mounted on a 15-Gallon Poly Tank

\*15 GAL. ONLY  
(Pump not included)

# MAINTENANCE MADE EASY



Maintenance is made easier with our YouTube video library, from installation and set-up to trouble shooting. Help with Rola-Chem equipment is a click away. [youtube.com/user/inforolachem](https://www.youtube.com/user/inforolachem)

SEE THESE AND OTHER  
"MAINTENANCE MADE EASY" PRODUCTS  
AT [ROLA-CHEM.COM](http://ROLA-CHEM.COM)

#### SPA VAC

Self-contained spa and pool vacuum  
Extends to over 7'

#### POOL SENTRY

Maintains water level,  
protecting pumps  
against burnout

#### ULTRA SCREEN

Catches debris and  
extends filter life

#### SCUMBUG

Removes scum line,  
devours grime and oils

# ROLA-CHEM™

[Rola-Chem.com](http://Rola-Chem.com) | 800-549-4473

5858 Centerville Rd • St. Paul, MN 55127 | Local: 651-653-5031 • Fax: 651-653-0989 | [info@Rola-Chem.com](mailto:info@Rola-Chem.com)